Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=LFL15869MTC1B787

LFL15869MTC1B787












Appearance & Shape









(1)(3) : GND (2) : OUT (4) : IN

A : Directional Input Mark

All the technical data and information contained herein are subject to change without prior notice

(in mm)



Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	180mm Paper Tape	10000



Features

Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Offering stable high selectivity up to very high frequency.

- 1. Low loss
- 2. Ultra-small, low-profiled, lightweight low-pass filters.
- 3. Ideal for removing high-frequency harmonics at power amplifier and IF stage.
- 4. Available in tape and reel packings for automatic mounting.
- 5. Absolutely no adjustment required.
- 6. Reflow solderable.
- 7. Center frequencies and responses are ready for customization. Samples are available in a short lead time.

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2018/09/28

Note: This datasheet may be out of date

Please download the latest datasheet of LFL15869MTC1B787 from the official website of Murata Manufacturing

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-global/products/productdetail?partno=LFL15869MTC1B787} \\$

LFL15869MTC1B787



Applications	GSM850 GSM900	
Nominal Center Frequency(fo)	869.50MHz	
Bandwidth(BW)	fo±45.50MHz	
Insertion Loss in BW I)	0.50dB max. (at 25°C)	
Insertion Loss in BW II)	0.60dB max. (-40 to +85°C)	
Attenuation(Absolute Value) I)	18.0dB min. at 2x(fo±45.5)MHz	
Attenuation(Absolute Value) II)	17.0dB min. at 3x(fo±45.5)MHz	
VSWR(max.)	1.7	
Characteristic Impedance(Nom.)	50Ω	
Power Capacity	3W	
Operating Temperature Range	-40℃ to 85℃	
L x W (size)	1.00x0.50mm	
Thickness(max.)	0.4mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2018/09/28


Note: This datasheet may be out of date


Please download the latest datasheet of LFL15869MTC1B787 from the official website of Murata Manufacturing

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-global/products/productdetail?partno=LFL15869MTC1B787} \\$

LFL15869MTC1B787







Frequency Characteristics

Spurious Response

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Signal Conditioning category:

Click to view products by Murata manufacturer:

Other Similar products are found below:

MAPDCC0001 MAPDCC0004 PD0409J5050S2HF 880157 HHS-109-PIN DC1417J5005AHF AFS14A30-2185.00-T3 AFS14A35-1591.50-T3 DS-323-PIN B39321R801H210 1A0220-3 JP510S LFB212G45SG8C341 LFB322G45SN1A504 LFL182G45TC3B746 SF2159E 30057 FM-104-PIN CER0813B MAPDCC0005 3A325 40287 41180 ATB3225-75032NCT BD0810N50100AHF BD2425J50200AHF C5060J5003AHF JHS-115-PIN JP503AS DC0710J5005AHF DC2327J5005AHF DC3338J5005AHF 43020 LFB2H2G60BB1C106 LFL15869MTC1B787 X3C19F1-20S XC3500P-20S 10013-20 SF2194E CDBLB455KCAX39-B0 TGL2208-SM, EVAL RF1353C 1E1305-3 1F1304-3S 1G1304-30 B0922J7575AHF 2020-6622-20 TP-102-PIN TP-103-PIN BD1222J50200AHF