

Product Search Data Sheet

NCP03WF683F05RL


In Production Recommended RoHS REACH

Note: This datasheet may be out of date. Please download the latest datasheet of NCP03WF683F05RL from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCP03WF683F05RL


Appearance & Shape





Packaging Information

Packaging		Standard Packing Quantity
RL	180mm Paper Tape	15000



- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-Constant
- 4. Reflow soldering possible
- 5. Lead is not contained in the product.

6. NCP series are recognized by UL/cUL (UL1434, File No.E137188).

Applications

Limited Usage	Mobile Application, Tablet PC, Wearable	
Other Usage	1. Temperature compensation for	
	transistor, IC and crystal	
	oscillator in mobile communications 2.	
	Temperature sensor for rechargeable	
	batteries	

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Rata Product Search Data Sheet

NCP03WF683F05RL

Note: This datasheet may be out of date. Please download the latest datasheet of NCP03WF683F05RL from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCP03WF683F05RL

Specifications

Resistance (25°C)	68kΩ
Resistance Value Tolerance (at 25°C)	±1%
B-Constant (25/50°C)	4250K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C) (Reference Value)	4303K
B-Constant(25/85°C) (Reference Value)	4311K
B-Constant(25/100°C) (Reference Value)	4334K
Max. Voltage	5V
Maximum Operating Current (25℃)	0.038mA
Typical Dissipation Constant (25℃)	1mW/°C
Operating Temperature Range	-40°C to 125°C
Size Code (in mm)	0.6x0.3mm
Size Code (in inch)	0.2x0.1inch
Shape	SMD
Mass	0.00026g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.







Product Search Data Sheet


NCP03WF683F05RL

Note: This datasheet may be out of date. Please download the latest datasheet of NCP03WF683F05RL from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCP03WF683F05RL







Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for NTC (Negative Temperature Coefficient) Thermistors category:

Click to view products by Murata manufacturer:

Other Similar products are found below :

 118-253FAJ-P01
 121-202EAC-P01
 123-802EAJ-P01
 128-105NDP-Q02
 135-503LAD-J01
 B57250V2473F560
 B57620C472K962

 A1004SG22P0
 199-303KAF-A02
 30054-4
 B57423V2473H062
 B57471V2474H062
 B57620C5223J062
 500-52AA04-101
 526-31AA19-104

 526-31AN12-202
 103AT-5-1P-FT
 111-802EAJ-901
 112-103FAG-H02
 112-104KAG-B01
 11028414-00
 111-182CAG-H01
 112-103FAF

 H01
 112-104KBF-F01
 118-202CAJ-P01
 526-31AA79-102
 B57442V5103J62
 517-59CL01-202
 B57401V2103H62
 11032565-00

 194303KEVA01
 NTCACAPE3C90193
 USP11595
 B57359V2224J260
 B57343V5103J360
 50070974-003-01
 189-602LDR-A01

 B57621C5472K062
 135-105QAF-J02
 B57421V2153J062
 B57230V2103H260
 B57471V2684H062
 B57471V2333H062
 126-153YJC-B01

 NTCS0603E3333FHT
 118-802EAJ-P01
 121-103FAC-Q02
 144-101FAG-001
 526-31AD07-153
 521-53AW02-104