
Data Sheet


EMIFIL® (Capacitor type) Single Circuit Type for Signal Lines

NFM3DC Series (1205 Size)


Dimensions



■ Insertion Loss Characteristics (Main Items)



■ Equivalent Circuit



Packaging

Code	Packaging	Minimum Quantity	
L	180mm Embossed Tape	4000	
В	Bulk(Bag)	500	

■ Rated Value (□: packaging code)

Part Number	Capacitance	Rated Current	Rated Voltage	Insulation Resistance (min.)	Operating Temperature Range
NFM3DCC220U1H3□	22pF 50/-20%	300mA	50Vdc	1000M ohm	-55 to +125°C
NFM3DCC470U1H3□	47pF 50/-20%	300mA	50Vdc	1000M ohm	-55 to +125°C
NFM3DCC101U1H3□	100pF 50/-20%	300mA	50Vdc	1000M ohm	-55 to +125°C
NFM3DCC221R1H3□	220pF 50/-20%	300mA	50Vdc	1000M ohm	-55 to +125°C
NFM3DCC471R1H3□	470pF 50/-20%	300mA	50Vdc	1000M ohm	-55 to +125°C
NFM3DCC102R1H3□	1000pF 50/-20%	300mA	50Vdc	1000M ohm	-55 to +125°C
NFM3DCC222R1H3□	2200pF 50/-20%	300mA	50Vdc	1000M ohm	-55 to +125°C
NFM3DCC223R1H3□	22000pF 50/-20%	300mA	50Vdc	1000M ohm	-55 to +125°C

Number of Circuit: 1

Continued on the following page. \nearrow



This data sheet is applied for CHIP EMIFIL® used for General Electronics equipment for your design.

- 1. This datasheet is downloaded from the website of Murata Manufacturing co., Itd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

Data Sheet

Continued from the preceding page.

■ ①Caution/Notice

Do not use products beyond the rated current and rated voltage as this may create excessive heat and deteriorate the insulation resistance.

Notice

Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin melting point is used. Please confirm the solderability of Tin plating termination chip before use.

This data sheet is applied for CHIP EMIFIL® used for General Electronics equipment for your design.

- 1. This datasheet is downloaded from the website of Murata Manufacturing co., Itd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Feed Through Capacitors category:

Click to view products by Murata manufacturer:

Other Similar products are found below:

PSM4-402Z-20B CKD110JB1E470S CKD510JB1E473S CKD510JB1H221S CKD510JB1H470S 4700-003MLF 4700-053LF 4701001MLF 4701-002MLF SSM1-402E-10B SSM1-501P-10T1 SSM1-402E-10T1 SSM1-152P-05T1 4700-009MLF SSM1-101Z-05B SSM1F402E-10T1 SSM1-202P-05T1 0805J0500471MATE03 PSM4-103Z-20T0 0805J1000470MATE03 SF0603C101SBNBB PSM4F-402Z-20T0
CX0603MRX7R6BB104 CX1206MKX7R9BB104 CX0603MRX7R9BB103 YFF15PC0J105MT000N NFM15CC222D1A3D
NFM15CC223C1C3D NFM15CC223C1A3D NFM18PC225B1A3D CX0603MRX5R6BB224 CX0603MRX7R9BB103
CX0805MRX7R0BB103 CX0805MRX7R8BB223 CX1206MKX7R7BB224 CX1206MKX7R9BB104 NFM31HK104R1H3L
NFM31HK223R1H3L NFM15PC224R1A3D DSS1NB32A223Q91A DSS1NB31H104Q91A NFE31PT101C1E9L NFE31PT220R1E9L
NFE61PT330B1H9L NFE61PT681B1H9L NFM31KC104R1H3L NFM41CC223R2A3L DSS1NB32A103Q91A DSS1NB32A102Q91A
NFE31PT471F1E9L