

Data Sheet

EMIFIL[®] (Capacitor type) Single Circuit Type for Signal Lines NFM41C Series (1806 Size)

Dimensions



Equivalent Circuit



■ Rated Value (□: packaging code)

Part Number	Capacitance	Rated Current	Rated Voltage	Insulation Resistance (min.)	Operating Temperature Range
NFM41CC220U2A3	22pF 50/-20%	300mA	100Vdc	10000M ohm	-55 to +125°C
NFM41CC470U2A3	47pF 50/-20%	300mA	100Vdc	10000M ohm	-55 to +125°C
NFM41CC101U2A3	100pF 50/-20%	300mA	100Vdc	10000M ohm	-55 to +125°C
NFM41CC221U2A3	220pF 50/-20%	300mA	100Vdc	10000M ohm	-55 to +125°C
NFM41CC471R2A3	470pF 50/-20%	300mA	100Vdc	10000M ohm	-55 to +125°C
NFM41CC102R2A3	1000pF 50/-20%	300mA	100Vdc	10000M ohm	-55 to +125°C
NFM41CC222R2A3	2200pF 50/-20%	300mA	100Vdc	10000M ohm	-55 to +125°C
NFM41CC223R2A3	22000pF 50/-20%	300mA	100Vdc	10000M ohm	-55 to +125°C

Number of Circuit: 1

Continued on the following page. $\boxed{\ensuremath{\nearrow}\xspace}$

This data sheet is applied for CHIP EMIFIL® used for General Electronics equipment for your design.

/Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.


2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.



<u>mnRata</u> Murata Manufacturing Co., Ltd.

http://www.murata.com/

Insertion Loss Characteristics (Main Items)



Packaging

Code	Packaging	Minimum Quantity
L	180mm Embossed Tape	4000
В	Bulk(Bag)	500

Data Sheet

Continued from the preceding page.

■ ①Caution/Notice

Do not use products beyond the rated current and rated voltage as this may create excessive heat and deteriorate the insulation resistance.

Notice

Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin melting point is used. Please confirm the solderability of Tin plating termination chip before use.

2

This data sheet is applied for CHIP EMIFIL® used for General Electronics equipment for your design.

/Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Feed Through Capacitors category:

Click to view products by Murata manufacturer:

Other Similar products are found below :

4700-003MLF 4700-053LF 4701-001MLF 4701-002MLF 0805J1000101MCTE01 SSM1-402E-05B SSM1-402E-10B SSM1-501P-10T1 SSM1-402E-10T1 SSM1-152P-05T1 4700-009MLF SSM1-101Z-05B SSM1F-402E-10T1 SSM1-202P-05T1 0805J0500471MATE03 PSM4-103Z-20T0 0805J1000470MATE03 SSM1-402Z-10T1 PSM4F-402Z-20T0 NFM31HK103R2A3L NFM15CC222D1C3D NFM18PC225B1A3D NFM18PS105D0J3D NFM18CC101R1C3D/BKN CX0603MRX5R6BB224 CX0603MRX7R9BB103 CX0805MRX7R0BB103 CX1206MKX7R7BB224 0805J0500473MXTE03 0805J0500223MXTE03 0805J1000102MXTE07 CX0603MRX7R0BB472 PSM4-103Z-20B DSS1NB32A223Q91A DSS1NB31H104Q91A NFE61PT330B1H9L NFM21HC223R1H3D NFM21PC225B0J3D NFM31KC104R1H3L NFM3DCC102R1H3L NFM3DCC223R1H3L NFM3DPC223R1H3L NFM41CC471R2A3L DSS1NB32A102Q91A NFM18CC222R1C3D NFM18PS474R0J3D NFM21HC105R1C3D NFM21PC224R1C3D NFM31KC104R2A3L NFM31KC223R1H3L