

PKM13EPYH4000-A0

Note: This datasheet may be out of date.

Please download the latest datasheet of PKM13EPYH4000-A0 from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=PKM13EPYH4000-A0











Appearance & Shape









Manufacturing Co., Ltd.

Features

Taking advantage of extensive automatic insertion design technology and materials experience, Murata has developed standard taping type piezoelectric sounders. This Murata technology supports labor and cost saving activities.

Features

- 1. Lead dimension: Improved mouting reliability (cut & clinch) due to round terminal
- 2. High and stable mountability
- 3. Ammo packaging



Applications

Other Usage Consumer/Industrial



Packaging Information

Packaging	Specifications	Standard Packing Quantity
-A0	Radial Taping	500

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ PKM13EPYH4000-A0\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=PKM13EPYH4000-A0

PKM13EPYH4000-A0



Specifications

Oscillation circuits	Not built-in	
Oscillation circuits	Not built-in	
Size	φ12.6×6.9 mm	
Frequency	4.0kHz	
Sound Pressure Level	78dB (typ.)	
Sound Pressure Level	70dB (min.)	
Measure Condition of Sound Pressure Level	[±1.5Vo-p,4.0kHz,square wave, 10cm]	
Capacitance	5.5nF	
Capacitance Tolerance	±30%	
Measurement Condition of Capacitance	[1kHz]	
Maximum input voltage	±15.0Vo-p max.	
Operating Temperature Range	-40°C to 85°C	
Storage Temperature Range	-40°C to 85°C	
Shape	Lead	
Lead Shape	Pin type	
Drive Type	External Drive	
EIAJ Part Number	PS-RP2-C13-40	
Mass	799mg	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




PKM13EPYH4000-A0

Note: This datasheet may be out of date.

Please download the latest datasheet of PKM13EPYH4000-A0 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=PKM13EPYH4000-A0





The following are examples of externally driven circuits.

- (1) Unstable multi-vibrator using Tr.
- (2) Circuits using inverters or NAND gates.



Frequency Response

Recommended Circuit

3 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Piezo Buzzers & Audio Indicators category:

Click to view products by Murata manufacturer:

Other Similar products are found below:

6-4 68S1240-PA MBA-624 FDG06PSLLF FDG111PLF F/NRMB 24 BLACK LF PF-35N29WQ PFD-21A29W PFD-27A35PQ PL-21N30WQ PL-27A35PSQ PLD-21N30WQ PS-531Q PT-3534FP EBPT-401 B822B PB-1220PEQ S6109 SBM616PR SC110E SC2036ACP SC616N-2 SC628FW SC628MPG SC648D SCS045MD9DT3S FCM12PLF F/EB20P-DR LF F/SMD03A LF FSMD8585JSLF F/SU 21-02 LF F/TCW 12 WITH LABEL LF F/UCW 06 WITH LABEL LF PFD-27N36W PKM22EPPH40S1-B0 PKM35-4A0 PL-35N29WQ PS-552Q CM-5 REF-202 B/SE 128 RED LF KBS-20DA-7AS KBS-27DA-5C-105 LSC628ANR 03-810.001 RTO-1R07-001 PL-21N31PQ B/CP 28B BLACK LF F/DGX 05P WITH LABEL LF