


Product Search Data Sheet


PTGL07AR820M9A51B0

discontinued RoHS REACH

Appearance & Shape







(in mm)

Note: This datasheet may be out of date. Please download the latest datasheet of PTGL07AR820M9A51B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=PTGL07AR820M9A51B0



 Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
 Circuit is protected until current is turned off.

3. Restores the original low resistance value automatically once the overload is removed.

4. Non-contact design leads to long life and no noise.

Durable and strong against mechanical vibration and shock because it is a solid element.



Limited Usage

Consumer Grade



Packaging Information

Packaging	Specifications	Standard Packing
		Quantity
B0	Bulk(Bag)	300

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





PTGL07AR820M9A51B0

Note: This datasheet may be out of date. Please download the latest datasheet of PTGL07AR820M9A51B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=PTGL07AR820M9A51B0

Specifications

Max. Voltage	265V
Hold Current(25°C)	75mA
Measure Condition of Hold Current	(at +25°C)
Hold Current (2)	60mA
Measure Condition of Hold Current (2)	(at +60°C)
Trip Current(25°C)	125mA
Measure Condition of Trip Current	(at +25°C)
Trip Current(2)	150mA
Measure Condition of Trip Current(2)	(at -10°C)
Max. Current	0.5A
Resistance (25°C)	82Ω
Resistance Value Tolerance (at 25°C)	±20%
Curie Point(typ.)	120°C
Power Consumption(typ)	1.4W
Operating Temperature Range	-10°C to 60°C
D: Outer Dimension	8.2mm
Thickness	6.5mm
F: Lead Space	5mm
d: Lead Diameter	0.5mm
Shape	Lead
Mass	0.64g
MSL	Ν

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






Product Search Data Sheet


PTGL07AR820M9A51B0

Note: This datasheet may be out of date. Please download the latest datasheet of PTGL07AR820M9A51B0 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=PTGL07AR820M9A51B0







Resistance-Temperature Charac.



Operating Time (Typical Curve)

Protective Threshold Current Range

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for PTC (Positive Temperature Coefficient) Thermistors category:

Click to view products by Murata manufacturer:

Other Similar products are found below :

 PTCAUX7-36-5C
 PTCCL09H251FBE
 PTCTL3MR100GTE
 PTCCL05H630HTE
 B59346A1502P020
 PTCTT95R100GTE

 PTCLL05P131TBE
 PTCCL09H541DBE
 TFPT0805L1800FV
 B59725T1120A062
 B59116S0225B010
 B59008C0150A040

 B59100M1090A070
 B59100M1145A070
 B59873C0120A070
 102PS1G
 B59300M1150A070
 B59339A1501P020
 B59770B0120A070

 B59985C0120A070
 B59995C0120A070
 YQR100R060
 YQS5751PTO
 YQS5856PTF
 YQS5930PTO
 YS5675
 YS5918PTO
 YQS5898PTO

 YQS5868PTF
 YQD100N1000
 KTY81/210,112
 B59010D1135B40
 B59606A110A62
 B59807A90A62
 B59830C120A70
 B59874C120A70

 B59960C160A70
 YQD120N0025
 PTGL12AR270M9C01B0
 PTGL12AR100M6C01B0
 PTGL07AS2R7K2B51A0
 PTGL07AS1R8K2B51B0

 PTS120601B100RPU00
 PTGL10AR3R9M3P51B0
 PTGL07BD220N3B51B0
 PTGL07AS5R6K4B51B0
 PTGL07AS150K6B51A0

 PTGL07AR8R2M3P51B0
 PTGL07AR560M9A51B0
 PTFL04BD471Q2N34B0
 PTGL07AS150K6B51A0