Note: This datasheet may be out of date.

Please download the latest datasheet of SFPKA455KD4A-R1 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=SFPKA455KD4A-R1

SFPKA455KD4A-R1










Appearance & Shape







Features

The SFPKAseries is comprised of small, high-performance, economical, thin (5.0mm) filters consisting of 4 ceramic elements. Their innovative construction is perfect for shrinking mobile communication products such as cordless phones, pagers and transceivers.

Features

- 1. The filters are mountable by automatic placers.
- 2. The filters can be reflow soldered and withstand washing.
- 3. They are slim, at only 5.0mm maximum thickness.
- 4. The bandwidth ranges from D to H.
- 5. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)



Applications

Other Usage Communication Equipment



Packaging Information

Packaging	Specifications	Minimum Order Quantity
-R1	330mm Embossed Tape	1000

1 of 3

Attentior

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date. ${\it Please download the latest datasheet of SFPKA455KD4A-R1 from the official website of Murata}$ Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=SFPKA455KD4A-R1

SFPKA455KD4A-R1



Specifications

Operating Temperature Range	-20°C to 80°C	
Shape	SMD	
Elements	4	
Center Frequency	455.0kHz	
Center Frequency Tolerance	±1.5kHz	
Nominal Center Value	No	
6dB Bandwidth	fn±10.0kHzmin.	
Stop Bandwidth	20.0kHz	
Area of Stop Bandwidth	[within 40dB]	
Stop Band Attenuation	27dB[within fn±100kHz]	
Insertion Loss	4.0dB[at minimum loss point]	
Ripple	2.0dB[within fn±7kHz]	
Input/Output Impedance	1500Ω	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date.


Please download the latest datasheet of SFPKA455KD4A-R1 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=SFPKA455KD4A-R1

SFPKA455KD4A-R1








Frequency Characteristics

Spurious Response



Measurement Circuit

3 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Signal Conditioning category:

Click to view products by Murata manufacturer:

Other Similar products are found below:

MAPDCC0004 PD0409J5050S2HF 880157 HHS-109-PIN DC1417J5005AHF DC4859J5005AHF AFS14A30-2185.00-T3 DS-323-PIN DSS-313-PIN B39321R801H210 B39921B4317P810 1A0220-3 2089-6207-00 JP510S LFB212G45SG8C341 LFB322G45SN1A504 LFL182G45TC3B746 SF2159E 30057 1P510S CER0813B 3A325 40287 41180 ATB3225-75032NCT B69842N5807A150 BD0810N50100AHF BD2425J50200AHF C5060J5003AHF JHS-114-PIN JHS-115-PIN JP503AS DC0710J5005AHF DC2327J5005AHF DC3338J5005AHF 43020 LFB2H2G60BB1C106 LFL15869MTC1B787 X3C19F1-20S XC3500P-20S 10013-20 SF2081E SF2194E SF2238E CDBLB455KCAX39-B0 RF1353C PD0922J5050D2HF 600S150FTRB 1E1305-3 1F1304-3S