

CB34 EX

2-Port CAN to Ethernet Server

100 Version



DATASHEET

Key Points

- Serial to Ethernet server
- CAN device support (programming required)
- DeviceNet compliant
- RS-232 and RS-422/485 serial device support
- Works out of the box - no programming is required
- Metal enclosure
- Rebrand with your custom product label
- Customize with development kit

Note: Programming required for products which use CAN

Features

- Power via two position terminal block, TSTRIP5, serial port, or barrel connector
- 10/100Mbps Ethernet
- TCP/UDP/Telnet modes
- DHCP/Static IP modes
- Web Based Configuration
- 32-bit performance
- Industrial Temperature Range (-40°C to 85°C)

Optional

The following options are available with the optional development kit:

- Customize any aspect of operation including web pages, data filtering, or custom network applications
- Additional baud rates
- CAN device support
- eTPU coprocessor
- Two bi-color programmable LEDs

The following optional software modules are not included with kit and are sold separately:

- Embedded SSL & SSH Security Suite (Module License Version)
- SNMP



Factory Application Specifications

Serial Port Baud Rate

Factory application supports up to 115,200 baud. Custom rates available with development kit.

Serial Protocols Supported

RS-232, RS-422, RS-485, DeviceNet compliant and CAN (programming required)

Serial Configurations

The two UARTs can be configured in the following ways:

- One RS-232 port, one RS-485 port
- One RS-485 port (full or half duplex on TSTRIP5), one RS-485 port (half-duplex on DB9)
- One RS-232 port, one CAN port (programming required)
- One RS-485 or RS-232 port, one CAN port (programming required)

Hardware Specifications

Processor & Memory

32-bit Freescale ColdFire 5234 running at 147.5MHz with 8MB SDRAM, and 2MB Flash.

Network Interface

10/100 BaseT with RJ-45 connector

Data I/O Interface

- Two UARTs
- CAN Interface

Storage

MicroSD/MMC Flash Card Interface (with SDHC support)

LEDs

Link, speed/data, power, and two bi-color general purpose programmable LEDs

Physical Characteristics

Dimensions (inches): 4.20" x 3.25" x 1.00"

Power

DC Input Voltage: 7V-24V

Environmental Operating Temperature

-40° to 85° C

RoHS Compliance

The Restriction of Hazardous Substances guidelines ensure that electronics are manufactured with fewer environment harming materials.

Agency Approvals

UL, C/UL, CE, FCC



Front and Back Panel



Connector Interface Description and Pinouts

The hardware has support for three serial interfaces: UART0 (RS-232), UART1 (RS-485/422) and CAN. Each serial interface can be configured via internal jumpers to appear on either the Terminal Strip 5 or DB9 connector.

Table 1: Connector Description

Connector	Description	Default Setting
Port 0	Terminal Strip 5 (TSTRIP5)	UART 1 RS-485 Half Duplex
Port 1	DB9 Connector	UART 0 RS-232
Power Input 1	Barrel connector	Default power source

Table 2: Serial Port Connector (Port 0 TSTRIP5) Pinout and Signal Description¹

Pin	UART 0 RS-232	UART 1 RS-485	CAN	Description
1	GND	GND	GND	Ground
2	RX	HD/FD TX-	CANL	Receive or Half Duplex or Full Duplex Transmit Negative or CAN Low
3	TX	HD/FD TX+	GND	Transmit or Half Duplex or Full Duplex Transmit Positive or Ground
4	RTS	FD RX-	CANH	Request To Send or Full Duplex Receive Negative or CAN High
5	CTS or PWRIN ¹	FD RX+ or PWRIN ¹	PWRIN ¹	Clear To Send or Full Duplex Receive Positive or Raw DC Power Input

Note:

1. Optional power input

Table 3: Serial Port Connector (Port 1 DB9 Connector) Pinout and Signal Description¹

Pin	UART 0 RS-232	UART 1 RS-485	CAN	Description
1	CD	-	-	Carrier Detect
2	RX	HD/FD TX-	CANL	Receive or Half Duplex or Full Duplex Transmit Negative or CAN Low
3	TX	FD RX+	GND	Transmit or Full Duplex Receive Positive or Ground
4	DTR	-	-	Data Terminal Ready
5	GND	GND	GND	Ground
6	DSR	FD RX-	GND	Data Set Ready or Full Duplex Receive Negative or Ground
7	RTS	HD/FD TX+	CANH	Request To Send or Half Duplex or Full Duplex Transmit Positive or CAN High
8	CTS	-	-	Clear To Send
9	RI or PWRIN ¹	PWRIN ¹	PWRIN ¹	Ring Indicator or Raw DC Power Input

Note:

- Optional power input

Table 4: Power Connector (Power Input 1 Barrel Connector) Pinout and Signal Description¹

Pin	Signal	Description
Outer Shell	Negative	Ground
Center Pin	Positive	Raw DC Power Input

Note:

- Optional power input

Part Numbers

CB34 EX 2-Port Serial to Ethernet Server

Part Number: CB34-EX-100IR

DIN Rail Mounting Kit (100 Version, double sided)

Part Number: DIN-100

DIN Rail Mounting Kit (200 Version, single sided)

Part Number: DIN-200

CB34 EX Development Kit

Part Number: NNDK-CB34EX-KIT

Kit includes all the hardware and software you need to customize the included platform hardware. See NetBurner Store product page for package contents.

Embedded SSL & SSH Security Suite (Module License Version)

Part Number: NBLIC-SSL-MODULE

Available as an option if you are using a development kit.

SNMP V1 (Module License Version)

Part Number: NBLIC-SNMP

Available as an option if you are using a development kit.

Ordering Information

E-mail: sales@netburner.com

Online Store: www.NetBurner.com

Telephone: 1-800-695-6828

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Development Tools](#) category:

Click to view products by [NetBurner](#) manufacturer:

Other Similar products are found below :

[DP130SSEVM](#) [ISO3086TEVM-436](#) [ADP5585CP-EVALZ](#) [CHA2066-99F](#) [AS8650-DB](#) [MLX80104 TESTINTERFACE](#) [I2C-CPEV/NOPB](#)
[ISO35TEVM-434](#) [416100120-3](#) [XR18910ILEVB](#) [XR21B1421IL28-0A-EVB](#) [EVAL-ADM2491EEBZ](#) [MAXREFDES23DB#](#)
[MAX9286COAXEVKIT#](#) [MAX3100EVKIT](#) [MAX13235EEVKIT](#) [XR21B1424IV64-0A-EVB](#) [CMOD232+](#) [MAX13042EEVKIT+](#)
[MAX14838EVKIT#](#) [MAXCAM705OV635AAA#](#) [MAX9205EVKIT](#) [DS100BR111AEVK/NOPB](#) [DC241C](#) [MAX9286RCARH3DB#](#)
[DC1794A](#) [SN65HVS885EVM](#) [EVB81112-A1](#) [DFR0257](#) [XR22404CG28EVB](#) [ZLR964122L](#) [ZLR88822L](#) [EVK-U23-01S](#) [EVK-W262U-00](#)
[DC196A-B](#) [DC196A-A](#) [DC327A](#) [OM13585UL](#) [MAX16972AGEEVKIT#](#) [MARS1-DEMO3-ADAPTER-GEVB](#) [MAX7315EVKIT+](#) [PIM511](#)
[PIM536](#) [PIM517](#) [DEV-17512](#) [STR-FUSB3307MPX-PPS-GEVK](#) [MAXREFDES177#](#) [EVAL-ADM2567EEBZ](#) [EVAL-ADN4654EBZ](#)
[MAX2202XEVKIT#](#)