

# ATPLA-N

## ACTIVE RFID TRANSPONDER



The **ATPLA-N** active RFID transponder works with the **ACTS-2** long range reader. The transponder can send its ID automatically at the time specified in the configuration or after pressing the button. The ID is transmitted in the 869MHz (ISM) frequency band.



### Technical parameters

- ID lenght: 4B
- ID transmission: 869MHz frequency, reading range - up to 200m
- Dimensions: 54 x 85 x 7 (mm)
- Battery life: up to 3 years
- Works with ACTS-2 long range reader

NETRONIX

ATPLA-N

27 maja 2020, 14:21

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Netronix](#) manufacturer:*

Other Similar products are found below :

[ACTS-2](#) [AGEDI-B](#) [ANTENNA L112 50 MM](#) [COTER-E4I](#) [COTER-ECI](#) [CTU-D2R](#) [CTU-D2RM](#) [CTU-D4R](#) [CTU-D5N](#) [CTU-D5R](#) [CTU-M5N](#) [CTU-M5RM](#) [CTU-R5RM](#) [I2M-005](#) [MM-R5](#) [MW-D7G](#) [MW-R7B](#) [MW-R7G](#) [NANO-MS](#) [PAC-AUB](#) [PAC-DUB](#) [PAC-DUG](#) [PAC-PUB](#) [PLA-D6L](#) [PLA-MDK](#) [PLA-MDL](#) [PLA-R6L](#) [UW-D4G](#) [UW-DAL](#) [UW-R4G](#)