



## NAC3FCA-1

Lockable cable connector, power-in, screw terminals, blue, V-0 Insert

The powerCON is a locking 3 conductor equipment AC connector with contacts for line, neutral and pre-mating ground contact. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

### Features & Benefits

- Power-in (blue) and power-out (grey) versions with different keying to avoid the possibility of intermating
- Extremely robust and reliable
- Unique Neutrik chuck type strain relief
- UL, cUL recognized components  
VDE certified  
SEV approved
- Circuit Breaking Capability (IEC 61984) when mated with powerCON XX Series Receptacles
- Fast and easy twist lock latching system
- Ergonomic design
- Improved kink protection by two-component bushing
- V-0 Flammability rated insert

**Technical Information**

Product	
<b>Title</b>	NAC3FCA-1
<b>Gender</b>	female

Electrical	
<b>Contact resistance</b>	≤ 2 mΩ
<b>Dielectric strength</b>	4 kVdc / 2.8 kVac
<b>Insulation resistance</b>	> 10 GΩ (initial)
<b>Number of electrical contacts</b>	2 + PE
<b>Rating Europe</b>	EN 61984:20 A 250 V AC
<b>Rating USA</b>	UL 1977:20 A 250 V AC

Mechanical	
<b>Cable O.D.</b>	6 - 15 mm (1)
<b>Lifetime</b>	> 1000 mating cycles
<b>Wiresize</b>	2,5 mm <sup>2</sup>
<b>Wiresize</b>	12 AWG
<b>Locking device</b>	Quick Lock
<b>(1)</b>	Cable O.D. range limited to 6 mm - 14 mm acc. VDE

Material	
<b>Contact plating</b>	Ag
<b>Contacts</b>	Copper Alloy
<b>Insert</b>	Polyamide (PA 6.6)
<b>Locking element</b>	Zinc diecast
<b>Shell</b>	Polyamide (PA 6.6)
<b>Strain relief</b>	Polyacetal

Environmental	
Temperature range	-30 °C to +80 °C
Protection class	IP 20
Flammability Rating	UL 94 V-0

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [AC Power Plugs & Receptacles](#) category:*

*Click to view products by [Neutrik](#) manufacturer:*

Other Similar products are found below :

[739W-X2/03-BACK1](#) [85447L](#) [1301460003](#) [1301520016](#) [1301520008](#) [14W07](#) [15W07](#) [22806](#) [26W47](#) [929662-1](#) [27W75](#) [27W81](#) [962160-1](#)  
[29W08MB](#) [29W82](#) [26W](#) [26W76BLK](#) [27W47](#) [27W48](#) [28W](#) [28W81](#) [29W47MB](#) [HDR-E14FG1+](#) [30-9717-25](#) [43305](#) [85266](#) [5262DW](#) [22801](#)  
[22804](#) [25W47](#) [701W-15/06](#) [701W-20/27](#) [27T76](#) [739W-20/XX](#) [1301860536](#) [1301520018](#) [1301520021](#) [1301520020](#) [8210GY](#) [29W48](#) [3011-](#)  
[06](#) [A52S22A](#) [739W-X2/XX3](#) [26T49](#) [2707](#) [26W47-W](#) [1301450073](#) [RECWALLBOXBA](#) [1301490033](#) [30-1511](#)