



NAC3FPX-WOT-TOP

Appliance outlet connector, 1/4" flat tab terminals, without insulation divider

The powerCON TRUE1 TOP is a locking 16 A true mains connector for outdoor applications. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

The powerCON TRUE1 TOP is a connector with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live.

Features & Benefits

- IP65 rating and certified outdoor protection to UL50E enclosure type 4 (in mated condition or in combination with the rubber sealing cover SCNAC-FPX)
- Uses high impact UV-resistant materials
- Lockable 16 A single phase connector (USA: 20 A)
- Extremely robust and reliable
- ENEC certified according to IEC 60320

- Outdoor protection according to IP65 and UL50E enclosure type 4 (in mated condition or in combination with the rubber sealing cover SCNAC-FPX)
- True mains connector with breaking capacity (CBC)
- Easy and reliable twist lock system
- Unique Neutrik cable retention
- UL498 certified



Technical Information

| Product | |
|---------|-----------------|
| Title | NAC3FPX-WOT-TOP |

| Electrical | |
|-------------------------------|---------------------------------------|
| Contact resistance | ≤ 2 mΩ |
| Dielectric strength | 4 kVdc / 2.8 kVac |
| Insulation resistance | > 1 G Ω (after damp heat test) |
| Number of electrical contacts | 2 + PE |
| Rated current per contact | 16 A (USA: 20A) |
| Rated voltage | 250 V ac |

| Mechanical | |
|------------|----------------------|
| Lifetime | > 5000 mating cycles |
| Wiresize | 2.5 mm ² |
| Wiresize | 12 AWG |

| Material | |
|-----------------|-------------------------|
| Contact plating | 2 μm Ag |
| Locking element | Stainless steel |
| Shell | Polyamide (PA 6.6) |
| Contacts | Spring Copper (CuSn0.2) |

| Environmental | |
|-------------------|---|
| Flammability | UL 94 V-0 |
| Protection class | IP65, UL50E enclosure type 4 (mated or in combination with SCNAC-FPX) |
| Temperature range | -30 °C to +80 °C |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for AC Power Plugs & Receptacles category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below:

739W-X2/03-BACK1 85447L 1301460003 1301520016 1301520008 14W07 B293000N2 15W07 22806 929662-1 27W75 27W81 962160-1 29W08MB 29W82 26W 26W76BLK 27W47 27W48 28W 28W81 29W47MB HDR-E14FG1+ 30-9717-25 43305 85266 5262DW 22801 22804 25W47 701W-15/06 701W-20/27 26W75 27T76 29T48 739W-20/XX 1301860536 1301520018 1301520021 1301520020 8210GY 29W48 3011-06 A52S22A 739W-X2/XX3 26T49 2707 26W47-W 1301450073 RECWALLBOXBA