NEUTRIK



NADB9FF

9 pole D-SUB feedthrough, female to female, D-shape nickel housing

Features & Benefits

- Ideal for audio networking and integration of equipment into video systems
- Universally accepted standard D-shape housing

NEUTRIK

Technical Information

Product	
Title	NADB9FF
Gender	female - female

Electrical	
Contact resistance	30 mΩ
Insulation resistance	> 5 GΩ
Number of electronical contacts	9
Rated current per contact	3 A
Rated voltage	50 V ac
Dielectric strength	> 0.5 kVac

Mechanical	
Panel thickness	4 mm
Wiresize	
Wiring	Feedthrough
Mounting direction	Front mounting
Chassis shape	D

Material	
Contact plating	Au
Contacts	Brass (CuZn39Pb3)
Insert	Steel , tin plated, PBT
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel

Environmental	
Flammability	UL 94-V0
Temperature range	-25 °C to +85 °C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Adapters & Gender Changers category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below :

243A10120X 243A11070X 243A13290X 243A13460X 300X10729X 300X10759X GCHDLP26F26F 30-9532P 40-9586FP 500-135 40-9526HDMP 56F715-003 243A11800X 243A10560X 40-9526HDSP 243A11060X 243A10580X 56-725-001 SC485 173114-0088 173114-0099 76000670 76000700 NADB9MF 2902323 2902326 40-9538F NADB15FF-B NADB9FF-B 243A10030X 76000671 163A50029X 16-501373 FCC17-E09AD-210 FCE17-A15AD-250 FCE17-B25AD-210 FCE17-B25AD-250 FCE17B25AD290 FCE17-E09AD-210 FCE5709500430 2310387 GCHDLP44M44M GCLP25M25F FCC17A15AD2E0 FCC17C37AD280 FCC17-E09AD-280 FCC17E09AD293 FCC17E09AD4D0 FCE17-A15AD-290 FCE17-E09AD-240