



## NC3FPP

Product	
Connector Type	XLR
Gender	female
Electrical	
Capacitance between contacts	$\leq 4$ pF
Contact resistance	$\leq 3$ m $\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 2$ G $\Omega$ (initial)
Insulation resistance	$> 0.1$ G $\Omega$ (after damp heat test)
Rated current per contact	6 A
Rated voltage	50 V
Mechanical	
Insertion force	$\leq 20$ N
Withdrawal force	$\leq 20$ N
Lifetime	$> 1000$ mating cycles
Wiring	Solder contacts
Locking device	Retention spring
Mounting direction	front
Chassis shape	P
Material	
Contact plating	2 $\mu$ m Ag over 2 $\mu$ m Ni
Contacts	Bronze (CuSn6)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Steel Ck67
Environmental	
Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [neutrik](#) manufacturer:*

Other Similar products are found below :

[NC3MD-L-1-BAG](#) [CS-BNC-LCV](#) [NAOBO](#) [NC3FM-C-B](#) [NC3MBHL](#) [NC5FAV](#) [NC5FRC-B](#) [NC5FX-HD-B](#) [NDL8](#) [NF2D-B-9](#) [NKO2M-0-3](#) [NKTT04-BLK](#) [NKTT-05BU](#) [NKTT1-BLK](#) [NL4MP-B](#) [NP2CM-B](#) [NP2RX](#) [NP2RX-BAG](#) [NPPA-TT-S-FN](#) [NYS373-5](#) [FDR1](#) [CS-BNC](#) [3FD-H-I-B](#) [ML1](#) [NL4MP-1](#) [G038DB](#) [NA3FMX](#) [NC3FP-1-BAG](#) [NC6FC](#) [NCJ9FK-V](#) [NKTT-05GN](#) [NL4MP-M3](#) [NPPA-TT-IDC](#) [NA2FPMM/W](#) [NL4FC-B](#) [NYS373-9-U](#) [SCNAC-PX](#) [DIE-R-BNC-X](#) [NKPF-SR-B-2](#) [108E](#) [NBNC75BLP7-D](#) [NBTC75BVX6](#) [NC3FBV2-B](#) [MCON0164](#) [DIE-BNC-U](#) [DIE-R-BNC-PU](#) [NAM4](#) [BTXX](#) [NC3FX-1](#) [NC3MXX-HD-B-D](#)