NEUTRIK



NC3FAHR2-0

3 pole female XLR receptacle, grounding: separate ground contact to mating connector shell and front panel, lateral right PCB mount, Retention spring instead of latch

The 'State of the Art' receptacle. Round plastic body XLR PCB mount panel connector. These have the smallest size and highest packing density (23 mm between centres). New designed tulip type contacts with hard gold plating and polished contact areas. UL recognized component.

Features & Benefits

- Smallest XLR receptacles, highest packing density
- Tulip type female contact
- Housing flammability UL94V-0

- Plastic housing, steel retention spring
- Polished contact areas and hard gold plating



Technical Information

Product	
Title	NC3FAHR2-0
Connection Type	XLR
Gender	female

Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 6 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	6 A
Rated voltage	< 50 V
Grounding Options	Separate ground contact connected to mating connector shell and front panel, no connection to Pin 1

Mechanical	
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Locking force	> 20 separating force N
Wiresize	
Wiring	Laterial right PCB mount
Locking device	Retention spring
Mounting direction	Rear mounting
Chassis shape	A
Mounting	A-Screw



Material	
Contacts	Bronze (CuSn6)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Steel Ck67

Environmental	
Approvals	UL
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for XLR Connectors category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below:

707-0300 PPCB-H A3F01 A3M01 QGP3F AA3FL AAA4FWZ AAA4MWZ AC3-MIC AC4-MIC AC5FPZB AC6AFDZV D4FB

DE4MW DHNF-BAG E3MBAUSW NA3MP-UW NC3FBHR1-0 NC3FD-H-0 NC3FK-V NC3FXY-B NC3MK-V NC3MXY NC5FX
HD-B NC6MSX-BAG SL05 99.265.0400.0 A3F04 AC3FG AC4-FCP AC4FPZ AQG4F 2504FP 30-498-2 R6MZ 3FD-H-I 3FD-H-I-(0)

3FD-H-I-B 3FD-V-I 3FD-V-I-(0) 3FD-V-I-B 3MD-H-I-B 3MD-V-I 3MD-V-I-B TA01 TA3MWX TA5MLWX MINICCF8

TRASM4M1X TRASM7M1X