## NEUTRIK

## NC3MX-1-BAG

X-1 series - 3 pin male - black chrome housing/silver contacts.

NC3MX-1-BAG



## **Technical Information**

Product	
Title	NC3MX-1-BAG
Connection Type	XLR
Gender	male

Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 3 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	16 A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	3.5 - 8.0 mm
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 2.5 mm²
Wiresize	max. 14 AWG
Wiring	Solder contacts
Locking device	Latch lock

NC3MX-1-BAG 2/3



Material Mat	
Boot	Polyurethan
Contact plating	2 μm Ag
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Zinc diecast (ZnAl4Cu1)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black chromium
Strain relief	Polyacetal (POM)

Environmental	
Approvals	UL
Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

NC3MX-1-BAG 3/3

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for XLR Connectors category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below:

707-0300 8800235 91101181024 91201231 91214571 A3F01 A3M01 QGP3F HA16PRQ-3SE(71) AA3FL AAA4FWZ AAA4MWZ
AC3-MIC AC4-MIC AC5FPZB AC6AFDZV AC7FDZB D4FB DE4MW DHNF-BAG E3MBAUSW NA2FP-UW NA3MP-UW
NC3FBHR1-0 NC3FD-H-0 NC3FK-V NC3FX-1 NC3FXY-B NC3MDM3-H-B NC3MK-V NC3MXY NC4FD-LX-0 NC5FX-HD-B
NC6FSXX-BAG NC6MD-LX-BAG NC6MSX-BAG 91210071096 SL05 99.265.0400.0 A3F04 AC3FG AC3MMG AC4-FCP AC4FPZ
AQG4F 2504FP 30-498-2 R6MZ CXX-15 3FD-H-I