



## NC4MDM3-H

4 pole male receptacle, horizontal PCB mount, Nickel housing, silver contacts, M3 mounting holes

Universal D-size metal body XLR panel mount series. UL recognized component.

### Features & Benefits

- Robust "D" metal shell
- PCB mount termination
- Standardized D sized 24 mm panel cutout

**Technical Information**

Product	
Title	NC4MDM3-H
Connection Type	XLR
Gender	male

Electrical	
Capacitance between contacts	$\leq 7$ pF
Contact resistance	$\leq 5$ m $\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10$ G $\Omega$ (initial)
Rated current per contact	10 A
Rated voltage	$< 50$ V

Mechanical	
Insertion force	$\leq 20$ N
Withdrawal force	$\leq 20$ N
Lifetime	$> 1000$ mating cycles
Wiresize	
Wiring	Horizontal PCB mount
Locking device	Latch lock
Mounting direction	Rear mounting
Chassis shape	D
Mounting	Mounting holes with M3 threads

Material	
Contact plating	2 µm Ag over 2 µm Ni
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA66)
Locking element	Steel Ck67
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel

Environmental	
Approvals	UL
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Neutrik](#) manufacturer:*

Other Similar products are found below :

[103F](#) [103M](#) [103P](#) [104L](#) [108E](#) [203F](#) [203FM](#) [203M](#) [203P](#) [3FD-H-I](#) [3FD-H-I-\(0\)](#) [3FD-H-I-B](#) [3FD-L-I-\(O\)](#) [3FD-V-I](#) [3FD-V-I-0](#) [3FD-V-I-\(0\)](#)  
[3FD-V-I-B](#) [3MC-I](#) [3MD-H-I](#) [3MD-H-I-B](#) [3MD-V-I](#) [3MD-V-I-B](#) [8800235](#) [8MX6-T](#) [91101181024](#) [91201231](#) [91210071096](#) [91214571](#)  
[91303761006](#) [ACRF-1](#) [ACRF-2](#) [ACRF-3](#) [ACRF-4](#) [ACRF-5](#) [ACRF-6](#) [ACRF-7](#) [ACRF-8](#) [ACRF-9](#) [ACRM-1](#) [ACRM-2](#) [ACRM-3](#) [ACRM-4](#)  
[ACRM-5](#) [ACRM-6](#) [ACRM-7](#) [ACRM-9](#) [A-SCREW-1-8](#) [B220-0X-33](#) [B220-8X-33](#) [BP1](#)