NEUTRIK



NC5MX-TOP

5 pole male cable connector, TRUE OUTDOOR PROTECTION (TOP), gold contacts

The X-TOP series is a "heavy-duty" XLR cable connector for outdoor use. IP65 rating and certified outdoor protection to UL 50E by mating with related cable or chassis connector of the XLR TOP range.

Features & Benefits

- Heavy-duty sealed XLR connector range for harsh and demanding environment
- Uses high impact UV-resistant materials
- IP65 rating and certified outdoor protection to UL 50E (in combination with a TOP range counterpart)



Technical Information

Product	
Title	NC5MX-TOP
Connection Type	XLR
Gender	male

Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 3 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	7.5 A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	5.0 - 8.0 mm
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 1.0 mm ²
Wiresize	max. 18 AWG
Wiring	Solder contacts
Locking device	Latch lock



Material	
Bushing	UV-resistant rubber
Contact plating	0.2 μm Au hard alloy over 2 μm Ni
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 66)
Locking element	Stainless steel
Shell	Stainless steel
Strain relief	Polyacetal (POM)

Environmental	
Approvals	UL
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP65, UL50E enclosure type 4 (mated)
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for XLR Connectors category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below:

707-0300 PPCB-H A3F01 A3M01 QGP3F HA16PRM-3SG(71) AA3FL AAA4FWZ AAA4MWZ AC5FPZB AC6AFDZV D4FB

DE4MW DHNF-BAG E3MBAUSW NA3MP-UW NC3FBHR1-0 NC3FD-H-0 NC3FK-V NC3FXY-B NC3MK-V NC3MXY NC5FX
HD-B NC6MSX-BAG 99.265.0400.0 A3F04 AC3FG AC4-FCP AQG4F 2504FP R6MZ 3FD-H-I 3FD-H-I-(0) 3FD-H-I-B 3FD-V-I 3FD
V-I-(0) 3FD-V-I-B 3MD-H-I-B 3MD-V-I 3MD-V-I-B TA01 TA3MWX TA5MLWX MINICCF8 TRASM4M1X TRASM7M1X ML1

TS05TS BRT-L 3FD-L-I-(O)