#### NEUTRIK



# NC6FX

6 pole female cable connector with Nickel housing and silver contacts.

The "industry standard" XLR cable connector, easy to assemble with only 4 parts and no screws. Compact design with sturdy diecast shell, fibreglass reinforced hard plastic insert and chuck type strain relief for secure clamping of all cables.

### **Features & Benefits**

- Rugged zinc diecast shell, long lasting and durable
- Boot with rubber gland gives high protection against bending stresses
- UL recognized components

- Chuck type strain relief system for secure clamping of cables
- Coloured rings and boots available for coding and marking



# **Technical Information**

Product	
Title	NC6FX
Connection Type	XLR
Gender	female

Electrical	
Capacitance between contacts	≤ 7 pF
Contact resistance	≤ 3 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	7,5 A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	3.5 - 8.0 mm
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 1.0 mm <sup>2</sup>
Wiresize	max. 18 AWG
Wiring	Solder contacts
Locking device	Latch lock



Material	
Boot	Polyurethan
Contact plating	2 μm Ag over 2 μm Ni
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	St3K32 (latch) / Ck 67 (spring)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel
Strain relief	Polyacetal (POM)

Environmental	
Approvals	UL
Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for XLR Connectors category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below:

707-0300 PPCB-H A3F01 A3M01 QGP3F HA16PRM-3SG(71) AA3FL AAA4FWZ AAA4MWZ AC5FPZB AC6AFDZV D4FB

DE4MW DHNF-BAG E3MBAUSW NA3MP-UW NC3FBHR1-0 NC3FD-H-0 NC3FK-V NC3FXY-B NC3MK-V NC3MXY NC5FX
HD-B NC6MSX-BAG 99.265.0400.0 A3F04 AC3FG AC4-FCP AQG4F 2504FP R6MZ 3FD-H-I 3FD-H-I-(0) 3FD-H-I-B 3FD-V-I 3FD
V-I-(0) 3FD-V-I-B 3MD-H-I-B 3MD-V-I 3MD-V-I-B TA01 TA3MWX TA5MLWX MINICCF8 TRASM4M1X TRASM7M1X ML1

TS05TS BRT-L 3FD-L-I-(O)