



## NC6MX-BAG

6 pole male cable connector, black metal housing and silver contacts.

The "industry standard" XLR cable connector, easy to assemble with only 4 parts and no screws. Compact design with sturdy diecast shell, fibreglass reinforced hard plastic insert and chuck type strain relief for secure clamping of all cables.

### Features & Benefits

- Rugged zinc diecast shell, long lasting and durable
- Chuck type strain relief system for secure clamping of cables
- Boot with rubber gland gives high protection against bending stresses
- Coloured rings and boots available for coding and marking
- UL recognized components

**Technical Information**

| Product                |           |
|------------------------|-----------|
| <b>Title</b>           | NC6MX-BAG |
| <b>Connection Type</b> | XLR       |
| <b>Gender</b>          | male      |

| Electrical                          |                             |
|-------------------------------------|-----------------------------|
| <b>Capacitance between contacts</b> | $\leq 7$ pF                 |
| <b>Contact resistance</b>           | $\leq 3$ m $\Omega$         |
| <b>Dielectric strength</b>          | 1,5 kVdc                    |
| <b>Insulation resistance</b>        | $> 10$ G $\Omega$ (initial) |
| <b>Rated current per contact</b>    | 7,5 A                       |
| <b>Rated voltage</b>                | $< 50$ V                    |

| Mechanical              |                          |
|-------------------------|--------------------------|
| <b>Cable O.D.</b>       | 3.5 - 8.0 mm             |
| <b>Insertion force</b>  | $\leq 20$ N              |
| <b>Withdrawal force</b> | $\leq 20$ N              |
| <b>Lifetime</b>         | $> 1000$ mating cycles   |
| <b>Wiresize</b>         | max. 1.0 mm <sup>2</sup> |
| <b>Wiresize</b>         | max. 18 AWG              |
| <b>Wiring</b>           | Solder contacts          |
| <b>Locking device</b>   | Latch lock               |

| <b>Material</b>        |                            |
|------------------------|----------------------------|
| <b>Boot</b>            | Polyurethan                |
| <b>Contact plating</b> | 2 µm Ag over 2 µm Ni       |
| <b>Contacts</b>        | Brass (CuZn39Pb3)          |
| <b>Insert</b>          | Polyamide (PA 6.6 30 % GR) |
| <b>Locking element</b> | Zinc diecast (ZnAl4Cu1)    |
| <b>Shell</b>           | Zinc diecast (ZnAl4Cu1)    |
| <b>Shell plating</b>   | Black chromium             |
| <b>Strain relief</b>   | Polyacetal (POM)           |

| <b>Environmental</b>       |                           |
|----------------------------|---------------------------|
| <b>Approvals</b>           | UL                        |
| <b>Flammability</b>        | UL 94 HB                  |
| <b>Standard compliance</b> | IEC 61076-2-103           |
| <b>Protection class</b>    | IP 40                     |
| <b>Solderability</b>       | Complies with IEC 68-2-20 |
| <b>Temperature range</b>   | -30 °C to +80 °C          |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [XLR Connectors](#) category:*

*Click to view products by [Neutrik](#) manufacturer:*

Other Similar products are found below :

[707-0300](#) [PPCB-H](#) [A3F01](#) [A3M01](#) [QGP3F](#) [AA3FL](#) [AAA4FWZ](#) [AAA4MWZ](#) [AC3-MIC](#) [AC4-MIC](#) [AC5FPZB](#) [AC6AFDZV](#) [D4FB](#)  
[DE4MW](#) [DHNF-BAG](#) [E3MBAUSW](#) [NA3MP-UW](#) [NC3FBHR1-0](#) [NC3FD-H-0](#) [NC3FK-V](#) [NC3FXY-B](#) [NC3MK-V](#) [NC3MXY](#) [NC5FX-](#)  
[HD-B](#) [NC6MSX-BAG](#) [SL05](#) [99.265.0400.0](#) [A3F04](#) [AC3FG](#) [AC4-FCP](#) [AC4FPZ](#) [AQG4F](#) [2504FP](#) [30-498-2](#) [R6MZ](#) [3FD-H-I](#) [3FD-H-I-\(0\)](#)  
[3FD-H-I-B](#) [3FD-V-I](#) [3FD-V-I-\(0\)](#) [3FD-V-I-B](#) [3MD-H-I-B](#) [3MD-V-I](#) [3MD-V-I-B](#) [TA01](#) [TA3MWX](#) [TA5MLWX](#) [MINICCF8](#)  
[TRASM4M1X](#) [TRASM7M1X](#)