NEUTRIK





NE8FDV-TOP

Vertical PCB panel mount RJ45 receptacle, combined with sealing kit SE8FD-TOP, max. panel thickness 4 mm, mounting screws included.

The etherCON series is a ruggedized and lockable RJ45 connector system, optimized for pro audio, video and lighting network applications with IP65 rating and UL 50E certification. The chassis connectors are shaped to fit into standardized panels out of the entertainment industry. The D-series offers the most rugged design of the etherCON series and is perfectly suitable for panel mount and the installer market.

ATTENTION: Does not intermate with CAT6 cable connector NE8MC6-MO and NKE6S* cables.

Features & Benefits

- IP65 rating and certified outdoor protection to UL 50E (in combination with NE8MX-TOP or sealing cap closed)
- Accomodates NE8MCX* or any standard RJ45 plug
- Approved latch lock system
- Ground panel connection

- Uses high impact UV-resistant and gasket materials
- Class D or CAT5e according to ISO/IEC 11801 and TIA/EIA
- Mountable from the front of the panel



Technical Information

| Product | |
|---------|------------|
| Title | NE8FDV-TOP |
| Gender | female |

| Electrical | |
|---------------------------|------------------------|
| Contact resistance | < 10 mΩ |
| Dielectric strength | 1 kVdc |
| Frequency range | 1 - 100 MHz |
| Insulation resistance | > 0.5 GΩ |
| Rated current per contact | 1.5 A |
| Rated voltage | < 50 V |
| Transmission performance | Class D |
| Standard compliance | TIA/EIA 586B, IEC11801 |

| Mechanical | |
|------------------|-----------------------------|
| Insertion force | ≤ 20 N |
| Withdrawal force | ≤ 20 N |
| Lifetime | > 1000 mating cycles |
| Panel thickness | 2 mm - 4 mm , 0.08" - 0.16" |
| Wiring | vertical PCB mount |
| Locking device | Latch lock |

| Material | |
|-----------------|---------------------------|
| Contact plating | 0.2 μm Au over Ni plating |
| Contacts | Bronze (CuSn8) |
| Insert | PBTP 15 % GR |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell plating | Chromium |



| Environmental | |
|-------------------|--|
| Flammability | UL 94 V-0 |
| Solderability | Complies with IEC 68-2-20 |
| Temperature range | -30°C to +80 °C |
| Protection class | IP65, UL50E enclosure type 4 (mated or sealing cap closed) |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66-50 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS2-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 E5288-S000K3-L E5908-15A242-L 155302-001 AX100653