#### NEUTRIK



# **NL2FXX-W-S**

2 pole speakON cable connector, screw terminal assembly, chuck type strain relief for cable diameters 6 to 12 mm

speakON connectors are the industry-standard for loudspeaker connections. This product series offers extremely reliable and robust cable connectors with a proven twist lock system. speakON cable connectors feature solid contacts with screw-type terminals including a stranded wire protection







#### **Features & Benefits**

- Mates with 2-pole chassis connector as well as 4-pole chassis connector (contacts +1/-1)
- Ergonomic design with slip-proof twocomponent molded housing

Up to 37 A rms current rating

- Unique Neutrik locking bushing and strain relief for cable diameters 6 mm to 12 mm
- IEC 61984 certified, thus accepted as a component of equipment acc. to IEC 62368-1
- Superior NEUTRIK quality standard, extremely robust and reliable
- Easy and reliable twist lock system
- Easy to assemble because the strain relief locks with the insert mechanically and aligns with the housing
- Improved kink protection by twocomponent bushing

## **Assembly instruction video for speakON FXX**



## **Technical Information**

Product	
Title	NL2FXX-W-S
Connector series	speakON 2-pole

Electrical	
Contact resistance	≤ 2 mΩ
Dielectric strength	2.8 kVac
Insulation resistance	> 10 GΩ (initially)
Number of electronical contacts	2
Rating Europe	IEC 61984: 37 A 250 V AC
Rating USA	UL1977: 35 A 250 V AC
Rating Canada	CSA C22.2 No.182.3: 24 A 250 V AC
Attention	This product is strictly not intended for use as an AC mains or power supply connector!  CAUTION: NOT FOR INTERRUPTING  CURRENT

Mechanical	
Cable O.D.	6 – 12 mm
Lifetime	typically 5'000 mating cycles
Wiresize (mm)	1.5 – 4 mm²
Wiresize (AWG)	17 – 11 AWG
Locking device	Twist lock
Termination	screw type terminals



Material	
Contact plating	Ag
Contacts	Copper Alloy
Insert	Polyamide (PA6.6)
Locking element	Zinc diecast
Shell	Polyamide (PA6) / TPE
Strain relief	Polyketone
Bushing	Polypropylene / TPE

Environmental	
Temperature range	-33 °C to +80 °C
Protection class	IP20
Flammability acc. to UL94	V-0

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Loudspeaker Connectors category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below:

1479190-3 AP-4-11 AP-4-12 AP-4-14 AP-4-21 AP-4-22 AP-5-11 AP-5-13 AP-5-14 AP-5-21 AP-5-22 AP-6-11 AP-6-12 AP-6-14 AP-6-21 AP-6-22 AP-8-12 AP-8-13 AP-8-14 AP-8-21 BSL-0 BSL-1 BSL-2 BSL-3 BSL-4 BSL-5 BSL-6 BSL-8 BSL-9 BSL-WR CC-212 CC-215 CC-226 CL2160B TP/6 CS CL2160R TP/6 CS CP303010 CP303010X CP303011X EP-3-11P EP-3-12 EP-3-13P EP-3-14 EP-4-11P EP-4-11PB EP-4-12B EP-4-13P EP-4-13PB EP-4-14