

NMC-C-HR

Lockable USB Type-C chassis with integral USB IF approved receptacle



Features & Benefits

- Push Pull mating design provides secure locking system if mated with NMK-20U*
- Front and rear side mountable
- USB receptacle in scope of delivery
- Reversible USB-C housing
- Guiding housing for better protection of receptacles

Technical Information

| Product | |
|--------------|----------|
| Title | NMC-C-HR |

| Electrical | |
|----------------------------------|------|
| Rated current per contact | 5 A |
| Rated voltage | 20 V |
| Transmission Performance | null |

| Mechanical | |
|---------------------------|----------------------|
| Body Height | 3.16 mm |
| Body Length | 11.3 mm |
| Body Weight | 9.7 g |
| Orientation | Right Angle |
| PCB Mounting | HYBRID SMT+DIP |
| PCB surface center | 1.58 mm |
| Version | USB3.1 Gen.II |
| Lifetime | 10'000 mating cycles |
| Locking force | 50 N |
| Locking device | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Neutrik](#) manufacturer:

Other Similar products are found below :

[65-647-8-BK-BU](#) [950](#) [952](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [MUSBA511N5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [17-210051](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [MAB 8 SN V](#) [A-USB A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SMT-AS1N-W30](#) [4689-1](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBA81130](#) [33UBARS1-04SW11](#) [33UBAR-04SW11](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#) [MUSBB151341](#) [10135326-001LF](#) [M9177/3-1](#) [USB-A-S-F-B-VT](#) [925](#) [4198](#) [690-024-633-031](#) [KUSBEX-BSFS1N-W](#)