



NO2FW-XP

Female chassis connector with ruggedized anticorrosive plating, 4 crimp contacts, 1 XB2 feedthrough socket and 1 shell ground contact for SMPTE cable shield. Waterproof acc. to protection class IP68 in mated condition with sealing kit SCXP-F.

The chassis connector acts as a feedthrough allowing simplified installations by connecting a XB2 patch cable on the rear. The chassis cut-out has the same size as common standard broadcast cut-outs and is therefore simple to integrate into existing systems.

Additional dirt and dust protection: SCNO2FW-XP sealing cover.

[Now available!](#)

Features & Benefits

- Suggested OEM equipment connector with common broadcast cut-out
- Improved guiding nose for safe and correct connection
- Ruggedized and dirt protected hybrid feedthrough connection system
 - 1 MPO cut-out for XB2 patch cord
 - 2 signal contacts
 - 2 power contacts
 - 1 ground contact
- Designed as feedthrough for easy repair and replacement
- Suitable for indoor (studio) and outdoor (OB-Truck) camera links according to SMPTE Standard
- IP68 in mated condition with SCXP-F

DRAGONFLY Assembly Instruction - XB2

DRAGONFLY Assembly Instruction - IP68

DRAGONFLY Assembly Instruction - Crimping

Technical Information

Product	
Title	NO2FW-XP
Gender	female

Electrical	
Contact resistance	< 7 mΩ
Insulation resistance	> 10 GΩ (initial)
Mains	240V AC / 10A / 50Hz 120V AC / 10A / 60Hz 300V DC / 7A
Sense	42V AC peak / 1-3A / ≤1kHz 60V DC / 1-3A

Mechanical	
Insertion force	< 45 N
Withdrawal force	< 45 N
Lifetime	10'000 mating cycles
Locking force	900 N
Locking device	Push-Pull
Mounting direction	Front mounting
Chassis shape	Common standard Broadcast cut-out
Wiresize (power)	max. 16 AWG
Wiresize (sense)	max. 24 AWG

Material	
Contacts	Brass
Insert	Polyetherimide and Polycarbonate (PEI+PC)
Shell	Zinc diecast and Polyoxymethylen
Shell plating	Nickel

Environmental

Temperature range	-40 °C to +75 °C
--------------------------	------------------

Optical

Insertion loss	Typ. 0.6 dB per connection / Max. 1.0 dB per connection
Optical connector	XB2 Feedthrough

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fibre Optic Connectors](#) category:

Click to view products by [Neutrik](#) manufacturer:

Other Similar products are found below :

[0004700001](#) [6100-R](#) [6313](#) [F709722200](#) [F709730000](#) [F718183204](#) [F727403500](#) [F727752800](#) [8119](#) [9440F20-27S-190](#) [944-120-6001](#)
[9441F10SL-3S](#) [9444W28-21S](#) [9444W36-10S](#) [9446F10SL-4S](#) [9446W20-16S](#) [953-101-5310-P](#) [954-101-57202B](#) [A0270169](#) [12-9122](#) [12-5702](#)
[AX101713](#) [AX102420](#) [AX103923](#) [AX104024](#) [AX104193](#) [AX104230](#) [AX104562](#) [AX105203-B25](#) [AX105205-S1](#) [EHSC2M](#) [17-300800](#)
[181-011-126](#) [181-011-S](#) [181-057-126](#) [HRFC-R2\(40\)](#) [NKSOPBUY](#) [20500002116](#) [2064996-1](#) [20800001065](#) [2170](#) [9132](#) [2612](#) [2620](#) [9291](#)
[9440F16-10S](#) [9440F20-18S](#) [9446F16-10S-190](#) [953-106-50231](#) [953-120-5003](#)