NEUTRIK



NRJ3HF-1

1/4" stereo jack, unswitched, fully threaded nose, sleeve contact/front panel connection

Horizontal PCB panel mount jack featuring high board packing density by mounting on 15.88 mm (0.625 inch) minimum centers in rows or arrays. Mounting hardware must be ordered separately.

Features & Benefits

- High boarded packing densities
- Mounting nuts available in various styles
- A retentions spring ensures optimum grip on inserted plugs, avoiding the chance of lost connection



Technical Information

Product	
Title	NRJ3HF-1
Connection Type	Jack
Gender	female

Electrical	
Contact resistance	< 10 mΩ
Dielectric strength	1 kVdc
Insulation resistance	≥ 1 GΩ @ 500 V dc
Rated current per contact	3 A

Mechanical	
Insertion force	< 30 N
Withdrawal force	> 10 N
Lifetime	> 10000 mating cycles
Panel thickness	< 3 mm
Wiresize	
Wiring	Horizontal PCB mount
Locking device	Retention spring
Mounting direction	Rear mounting
Chassis shape	11.2 mm

Material	
Cap / Nut / Washer	PA 6.6 15% GR
Contact plating	2 μm Ag
Contacts	Bronze (CuSn6)
Shell	Polyamide (PA 6.6 30 % GR) UL 94 V0



Environmental	
Standard compliance	EIA RS 453, IEC 60603-11
Solderability	Complies with IEC 60068-2-20
Temperature range	-25 °C to +70 °C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Phone Connectors category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below:

M444B 6J1041A R4F E12BPKG ECP4PKG 161-3502L-E MT333X 171-0350-EX 171-101A-EX 171-3325-EX 176S NC3MG-V NYS228G P10834 P2380 P2381X P2411X P2412 P2724 JM2PB-AU BULK 9144 S2674 280L 163-158N-2-E 171-3308-EX 171-3500-E 2501FT CMT335 M10662 330Q RJ5VI-S 40116 TM1R-AU TM2PBMJ-AU TM2PJ-AU TM2PJ-AU BULK 4803.1351 49201 49205 TS3PBJ-AU TS3PBMJ-AU TT32BX 54B 40112 40205 415 XMT332B 52170017-331 570 NM3