NYS231LL

3 pole 3.5 mm plug, with x-large cable outlet, metal handle



Technical Information

Product	
Title	NYS231LL
Electrical	
Dielectric strength	0.5 kVdc
Insulation resistance	≥ 1 GΩ
Rated current	depends on mated connector
Contact resistance	depends on mated connector
Mechanical	
Cable O.D.	8 mm
Lifetime	1000 mating cycles
Environmental	
Flammability	Complies with IEC 68-2-20
Temperature range	-25 °C to +70 °C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Phone Connectors category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below :

 M444B
 6J1041A
 R4F
 128PKG
 RJ3VI
 E12BPKG
 ECP4PKG
 161-3300N-EX
 161-3502L-E
 161-7900HS-EX
 163-157J-E
 MT333X
 171

 0350-EX
 171-105AC-EX
 171-3325-EX
 171-6435-EX
 176S
 NC3MG-V
 NMJ4HFD2-NW
 NRJ4HH-1
 NS112BX
 NYS228G
 NYS352AG

 P10834
 P2380
 P2381X
 P2411X
 P2412
 P2724
 9144
 S2674
 163-156N-2-E
 163-158N-2-E
 171-0250-EX
 171-3308-EX
 171-3500-E
 171

 PA3191-2-E
 ST-3141-5N
 229
 2501FT
 CMT335
 M10662
 330Q
 RJ5VI-S
 40116
 TM1R-AU
 TM2PBMJ-AU
 TM2PJ-AU
 TM2PJ-AU

 BULK
 4803.1351

 40116
 TM1R-AU
 TM2PBMJ-AU
 TM2PJ-AU