



3 pole male right-angle XLR cable connector









## **Article Variations**

Article Name	Details	Packaging
RC3MR	Nickel plated housing, Silver plated contacts	Plastic bag
RC3MR-D	Nickel plated housing, Silver plated contacts	BULK
RC3MR-B	Black plated housing, gold plated contacts	Plastic bag
RC3MR-B-D	Black plated housing, gold plated contacts	BULK
RC3MR-BAG	Black plated housing, Silver plated contacts	Plastic bag
RC3MR-BAG-D	Black plated housing, Silver plated contacts	BULK



## **Technical Information**

Product	
Title	RC3MR
Connection Type	XLR
Gender	male

Electrical	
Insulation Resistance	> 1.5 GΩ
Contact Resistance	≤ 5 mΩ
Rated Current	10 A

Mechanical		
Lifetime	>1000 Mating Cycles	
Insertion Force	≤ 30 N	
Withdrawal Force	≤ 20 N	
Cable O.D.	4 - 7 mm	
Wiresize	1.5 mm <sup>2</sup>	
Wiresize	16 AWG	



Material	
Pin	Brass
Male Insert	PA6+30%GF UL94-HB
Ground Contact	Bronze
Housing	Zinc
Front Body	Zinc
Push Tube	PP
Cover	Zinc
Chuck	POM
Bushing	PA6+30%GF
Push Ring	POM
Boot	PVC
Pin	Sliver Plating
Ground Contact	Tin and Cer
Housing	Nickel Plating
Front Body	Nickel Plating
Cover	Nickel Plating

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for XLR Connectors category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below:

707-0300 AAA4FWZ AAA4MWZ AC3MMB-AU BULK AC5FPZB AC6AFDZV D4FB DE4MW E3MBAUSW 99.265.0400.0 A3F04
AC3FG AC4-FCP AQG4F 2504FP 30-498-2 R6MZ 3FD-V-I-B 3MD-V-I-B TA3MWX TA5MLWX TRASM4M1X TRASM7M1X ML1
3FD-L-I-(O) D6FDB DB25FTRS DHNF-BAG-MAD DHNF-BAG-O DHNM-BAG E3FBAUSW E3FSW E3MSW SR03 TA4FLWX
TA6FLWX TRAPC8M1X TRASM6M1X WP2S4P WP1S1 WP1B2 TA5FLWX NC3FEZY-P NC3FG-V NC6FSD-LX NC6MSD-LX
NCJ6FK-V NCXX-PROMO NA2FPMM/W NC3FD-L