

RC5F

5 pole female XLR cable connector



Article Variations

Article Name	Details	Packaging
RC5F	Nickel plated housing, Silver plated contacts	Plastic bag
RC5F-D	Nickel plated housing, Silver plated contacts	BULK
RC5F-B	Black plated housing, gold plated contacts	Plastic bag
RC5F-B-D	Black plated housing, gold plated contacts	BULK
RC5F-BAG	Black plated housing, Silver plated contacts	Plastic bag
RC5F-BAG-D	Black plated housing, Silver plated contacts	BULK

Technical Information

Product

Title	RC5F
Connection Type	XLR
Gender	female

Electrical

Contact Resistance	$\leq 5 \text{ m}\Omega$
Insulation Resistance	$> 1.5 \text{ G}\Omega$

Mechanical

Lifetime	>1,000 Mating Cycles
Insertion Force	$\leq 30 \text{ N}$
Withdrawal Force	$\leq 20 \text{ N}$
Cable O.D.	4 - 7 mm
Wiresize	1.5 mm ²
Wiresize	16 AWG

Material	
Plastic Body	PA6+30%GF
Jack	Brass
Ground Contact	Steel
Rubber Ring	Rubber
Button	Zinc
Housing	Zinc
Chuck	POM
Bushing	PA6+30%GF
Push Ring	POM
Boot	PVC
Jack	Sliver Plating
Ground Contact	Tin and Cer
Button	Nickel Plating
Housing	Nickel Plating

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [XLR Connectors](#) category:

Click to view products by [Neutrik](#) manufacturer:

Other Similar products are found below :

[AAA4FWZ](#) [AAA4MWZ](#) [AC5FPZB](#) [AC6AFDZV](#) [DE4MW](#) [E3MBAUSW](#) [99.265.0400.0](#) [AC3FG](#) [AC4-FCP](#) [AQG4F](#) [30-498-2](#) [R6MZ](#)
[3FD-V-I-B](#) [3MD-V-I-B](#) [TA01](#) [TA3MWX](#) [TA5MLWX](#) [TRASM4M1X](#) [TRASM7M1X](#) [ML1](#) [3FD-L-I-\(O\)](#) [D6FDB](#) [DB25FTRS](#) [DHNF-](#)
[BAG-MAD](#) [DHNF-BAG-O](#) [DHNM-BAG](#) [E3FBAUSW](#) [E3FSW](#) [E3MSW](#) [SR03](#) [TA4FLWX](#) [TA6FLWX](#) [TRAPC8M1X](#) [TRASM6M1X](#)
[WP2S4P](#) [WP1S1](#) [WP1B2](#) [TA5FLWX](#) [NC3FEZY-P](#) [NC3FG-V](#) [NC6FSD-LX](#) [NC6MSD-LX](#) [NCJ6FK-V](#) [NCXX-PROMO](#) [NA2FPMM/W](#)
[NC3FD-L](#) [NC3FD-L-0-1](#) [NC3FX-1-D](#) [NC3MX-1-D](#) [NC3MXY-B](#)