

## RCJ9FA

3 pole XLR female receptacle with 1/4" switching stereo jack



## Article Variations

| Article Name | Details                                   | Packaging |
|--------------|-------------------------------------------|-----------|
| RCJ9FA-H     | Horizontal PCB contacts, locking latch    | BULK      |
| RCJ9FA-H-0   | Horizontal PCB contacts, retention spring | BULK      |
| RCJ9FA-V     | Vertical PCB contacts, locking latch      | BULK      |
| RCJ9FA-V-0   | Vertical PCB contacts, retention spring   | BULK      |

## Technical Information

### Product

|                        |                 |
|------------------------|-----------------|
| <b>Title</b>           | RCJ9FA          |
| <b>Connection Type</b> | XLR/Jacks Combo |

### Electrical

|                                               |           |
|-----------------------------------------------|-----------|
| <b>Contact resistance - XLR</b>               | ≤ 15 mΩ   |
| <b>Contact resistance - 1/4" Jack</b>         | ≤ 25 mΩ   |
| <b>Dielectric strength</b>                    | 1500 V dc |
| <b>Insulation resistance - initial</b>        | ≥ 0.5 GΩ  |
| <b>Insulation resistance -after damp heat</b> | ≥ 0.2 GΩ  |
| <b>Rated current per Contact - XLR</b>        | 3 A       |
| <b>Rated current per Contact - 1/4" Jack</b>  | 3 A       |
| <b>Rated voltage</b>                          | 50 V ac   |

### Mechanical

|                           |                                                                                    |
|---------------------------|------------------------------------------------------------------------------------|
| <b>Lifetime</b>           | > 1'000 mating cycles                                                              |
| <b>Insertion force</b>    | ≤ 20 N                                                                             |
| <b>Withdrawal force</b>   | ≤ 20 N                                                                             |
| <b>Panel thickness</b>    | max. 3 mm (0.12")                                                                  |
| <b>Wiring</b>             | PCB mount                                                                          |
| <b>Locking device</b>     | Latch lock                                                                         |
| <b>Mounting direction</b> | Rear mounting                                                                      |
| <b>Mounting screw</b>     | Self-tapping Plastite® screw with thread 2.9 x 1.06 and tri-rondular configuration |

### Material

|                                    |                         |
|------------------------------------|-------------------------|
| <b>Shell</b>                       | PA 6.6 30% GR           |
| <b>Contacts</b>                    | CuSn6                   |
| <b>Contact plating - XLR</b>       | Au / Ag (G, TN, RN, SN) |
| <b>Contact plating - 1/4" Jack</b> | Au (TRS)                |
| <b>Locking latch</b>               | CK 65Mn steel           |

**Environmental**

|                              |                                   |
|------------------------------|-----------------------------------|
| <b>Flammability</b>          | UL 94 V0                          |
| <b>Operating temperature</b> | -20°C to +70°C                    |
| <b>Solderability</b>         | complies with IEC68-2-20          |
| <b>Environmental</b>         | complies with EU RoHS 2 and REACH |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [XLR Connectors](#) category:*

*Click to view products by [Neutrik](#) manufacturer:*

Other Similar products are found below :

[707-0300](#) [AAA4FWZ](#) [AAA4MWZ](#) [AC3MMB-AU BULK](#) [AC5FPZB](#) [AC6AFDZV](#) [D4FB](#) [DE4MW](#) [E3MBAUSW](#) [99.265.0400.0](#) [A3F04](#)  
[AC3FG](#) [AC4-FCP](#) [AQG4F](#) [2504FP](#) [30-498-2](#) [R6MZ](#) [3FD-V-I-B](#) [3MD-V-I-B](#) [TA3MWX](#) [TA5MLWX](#) [TRASM4M1X](#) [TRASM7M1X](#) [ML1](#)  
[3FD-L-I-\(O\)](#) [D6FDB](#) [DB25FTRS](#) [DHNFBAG-MAD](#) [DHNFBAG-O](#) [DHNMBAG](#) [E3FBAUSW](#) [E3FSW](#) [E3MSW](#) [SR03](#) [TA4FLWX](#)  
[TA6FLWX](#) [TRAPC8M1X](#) [TRASM6M1X](#) [WP2S4P](#) [WP1S1](#) [WP1B2](#) [TA5FLWX](#) [NC3FEZY-P](#) [NC3FG-V](#) [NC6FSD-LX](#) [NC6MSD-LX](#)  
[NCJ6FK-V](#) [NCXX-PROMO](#) [NA2FPMM/W](#) [NC3FD-L](#)