



RRE8F-Z

Female RJ45 receptacle with a front-mountable D-Size flange, gold plated contacts and IP65 rating to optimally protect your device or equipment from water ingress.





Features & Benefits

- D-shape metal flange
- IP65 rated outdoor protection when mated with related REAN IP65 connector or when covered with rubber cap
- UL94 V-0 rated materials
- Unique unified Rubber Cap & gasket design for providing more reliable protection functionality and an easier installation with device pane

Article Variations

Article Name	Details	Packaging
RRE8F-Z-000-0/1	Chrome plated housing, RJ45 Feedthrough	BULK / Plastic Bag
RRE8F-Z-001-0/1	Black plated housing, RJ45 Feedthrough	BULK / Plastic Bag

Technical Information

Product

Title	RRE8F-Z
Connection Type	Ethernet Receptacle
Gender	Female

Electrical

Contact resistance	$\leq 100 \text{ m}\Omega$
Dielectric strength	1 kVdc
Frequency range	1 – 100 MHz
Insulation resistance	$> 5 \text{ G}\Omega$ (initial)
Rated current per contact	1.5 A
Rated voltage	$< 50 \text{ V}$
Transmission performance	CAT 5E

Mechanical

Insertion force	$\leq 60 \text{ N}$
Withdrawal force	$\leq 60 \text{ N}$
Lifetime	> 1000 mating cycles
Wiring	Feedthrough
Locking device	Latch lock
Mounting direction	Front mounting
Chassis shape	See drawing
Panel Cutout	D

Material

Contact plating	AU
Contacts	Phosphor bronze
Insert	Polyamide (UL94-V0)
Locking element	Spring steel
Shell	Zinc diecast
Shell Plating	Chrome (-000) / Black (-001)

Environmental

Flammability	UL 94-V0
Protection class	IP65 (Mated or closed with rubber cap)
Standard compliance	TIA/EIA 586B, IEC 11801
Temperature range	-20 °C to +70 °C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modular Connectors](#) / [Ethernet Connectors](#) category:

Click to view products by [Neutrik](#) manufacturer:

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GDCX-PN-66](#) [GLX-A-44](#) [GLX-N-1010M-BLK](#) [GLX-S-88M-BLK](#)
[GMX-SMT4-N-88](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS-88-3.68](#) [PT-108A-8C-UL](#) [PTS-J531-8CS-50UL](#) [A-2014-0-4](#)
[GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [132764-001](#) [1413235](#) [MPS88RX-5000](#) [E5288-S000K3-L](#) [155302-001](#)
[AX101050](#) [AX101063](#) [AX101065](#) [AX101072](#) [AX101307](#) [AX101315](#) [AX101318](#) [AX102271](#) [AX102651](#) [AX102660](#) [AX104024](#) [203475](#)
[J0026D01ENL](#) [PC4D0018P](#) [KIT38082NI](#) [8949-B88/6](#) [2-6609208-5](#) [30-8956](#) [30-8964-100](#) [SM85](#) [17-103540](#) [191587](#) [PDI-68-RV](#) [PHP-](#)
[8P8C-S-5](#) [GAX-3-66-50](#)