

## RRE8F-Z-110

RJ45 Feedthrough receptacle , D-shape metal flange without latch lock

IP65 rating to optimally protect your device or equipment from water ingress. Air-tightness feature protect your device from Air ingress.



## Features & Benefits

- Robust design to withstand harsh environments and frequent use, ensuring long-lasting performance
- IP65 protection when mating with REAN Z series corresponding Ethernet connector or rubber cap closed
- UL94 V-0 rated materials
- Sealed chassis protects internal components and host devices from water damage, ensuring reliable and cost-effective performance in challenging environments
- The release latch function on the connector side makes it easy to connect and disconnect the RJ45 system, saving time and effort
- Network performance of Cat5e
- Rugged diecast shell with fashionable black plating

## Article Variations

Article Name	Details	Packaging
RRE8F-Z-110-0	Black plated housing, RJ45 feedthrough	BULK

## Technical Information

### Product

<b>Title</b>	RR8EF-Z-110
<b>Connection type</b>	Ethernet Receptacle
<b>Gender</b>	Female

### Electrical

<b>Contact resistance</b>	<100 mΩ
<b>Dielectric strength</b>	1 kVdc
<b>Frequency range</b>	1 – 100 MHz
<b>Insulation resistance</b>	> 0.5 GΩ
<b>Rated current per contact</b>	1.5 A
<b>Rated voltage</b>	< 50 V
<b>Transmission performance</b>	CAT 5e

### Mechanical

<b>Insertion force</b>	≤ 60 N
<b>Withdrawal force</b>	≤ 60 N
<b>Lifetime</b>	> 1000 mating cycles
<b>Panel thickness</b>	10mm
<b>Locking device</b>	Latch lock
<b>Wiring</b>	Feedthrough
<b>Chassis shape</b>	D

## Material

<b>Contact plating</b>	Gold plating
<b>Contacts</b>	Bronze
<b>Shell</b>	Zinc
<b>Insert</b>	PA66
<b>Shell plating</b>	Black plating

## Environmental

<b>Flammability</b>	UL94 V-0
<b>Standard compliance</b>	TIA/EIA 586B, IEC11801
<b>Protection class</b>	IP65 and Air tightness
<b>Temperature range</b>	-30 °C to +80 °C

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Modular Connectors](#) / [Ethernet Connectors](#) category:*

*Click to view products by [Neutrik](#) manufacturer:*

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GDCX-PN-66](#) [GLX-A-44](#) [GLX-N-1010M-BLK](#) [GLX-S-88M-BLK](#)  
[GMX-SMT4-N-88](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS-88-3.68](#) [PT-108A-8C-UL](#) [PTS-J531-8CS-50UL](#) [A-2014-0-4](#)  
[GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [132764-001](#) [1413235](#) [MPS88RX-5000](#) [E5288-S000K3-L](#) [155302-001](#)  
[AX101050](#) [AX101063](#) [AX101065](#) [AX101072](#) [AX101307](#) [AX101315](#) [AX101318](#) [AX102271](#) [AX102651](#) [AX102660](#) [AX104024](#) [203475](#)  
[J0026D01ENL](#) [PC4D0018P](#) [KIT38082NI](#) [8949-B88/6](#) [2-6609208-5](#) [30-8956](#) [30-8964-100](#) [SM85](#) [17-103540](#) [191587](#) [PDI-68-RV](#) [PHP-](#)  
[8P8C-S-5](#) [GAX-3-66-50](#)