

Features & Benefits

- D-shape metal shell
- Unique unified Rubber Cap&gasket design for providing more reliable protection functionality and an easier installation with device panel

Article Variations

Article Name	Details	Packaging
RRX5F-Z-000-0	Chrome plated housing, tin plated contacts	BULK
RRX5F-Z-001-0	Black plated housing, tin plated contacts	BULK
RRX5F-Z-002-0	Black plated housing, gold plated contacts	BULK

- Certified IP65 rating water protection when mating with related REAN IP65 connector or with rubber Cap covered
- UL94 V-0 rated materials

RRX5F-Z

IP65 protection

5 pole female XLR receptacle with D-Size Flange, solder cups and



Product		
Title	RRX5F-Z	
Connection Type	XLR	
Gender	Female	

Electrical

Contact resistance	$\leq 5 \text{ m}\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10 \text{ G}\Omega \text{ (initial)}$
Rated current per contact	7.5 A
Rated voltage	< 50 V

Mechanical	
Insertion force	≤ 60 N
Withdrawal force	≤ 60 N
Lifetime	1000 cycles
Wiring	Solder contacts
Locking device	Latch lock
Mounting direction	Front mounting
Chassis shape	D

Material	terial	
Contact plating	Tin (-000 & -001) / AU (-002)	
Contacts	Brass	
Insert	Polyamide (UL94-V0)	
Locking element	CK67 (spring)	
Shell	Zinc diecast	
Shell plating	Chrome (-000) / Black (-001 & -002)	



Environmental		
Flammability	UL94 V-0	
Protection class	IP65 (Mated or closed with rubber cap)	
Standard compliance	IEC 61076-2-103	
Solderability	Complies with IEC 68-2-20	
Temperature range	-20 °C to +70 °C	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for XLR Connectors category:

Click to view products by Neutrik manufacturer:

Other Similar products are found below :

AAA4FWZ AAA4MWZ AC5FPZB AC6AFDZV DE4MW E3MBAUSW 99.265.0400.0 AC3FG AC4-FCP AQG4F 30-498-2 R6MZ 3FD-V-I-B 3MD-V-I-B TA01 TA3MWX TA5MLWX TRASM4M1X TRASM7M1X ML1 3FD-L-I-(O) D6FDB DB25FTRS DHNF-BAG-MAD DHNF-BAG-O DHNM-BAG E3FBAUSW E3FSW E3MSW SR03 TA4FLWX TA6FLWX TRAPC8M1X TRASM6M1X WP2S4P WP1S1 WP1B2 TA5FLWX NC3FEZY-P NC3FG-V NC6FSD-LX NC6MSD-LX NCJ6FK-V NCXX-PROMO NA2FPMM/W NC3FD-L NC3FD-L-0-1 NC3FX-1-D NC3MX-1-D NC3MXY-B