

SPECIFICATIONS:
 Current rating:3.0A AC/DC
 Voltage rating:250V AC/DC
 Contact resistance:30m ohm MAX
 Insulation resistance:5000M ohm MIN
 Withstanding voltage:1000V AC for one minute
 Operating temperature range:-40°C~+85°C

MATERIAL AND FINISH
 Insulator:PBT+30%G.F(UL94V-0)
 Contact:Copper Alloy Nickel Undercoated Selective Gold Plated
 Finish:Metal Iron With Tin Plated

PART NO.:

Z-SUB DP * M * * * * *

NO. OF CONTACTS
 A=9PIN
 B=15PIN
 C=25PIN
 E=37PIN

MOUNTING OPTIONS
 1=RIVETED W/SHIELD ONLY
 2=RIVETED W/FRONT RIVET
 3=RIVETED W/REAR RIVET
 4=RIVETED W/NUT RIVET
 5=RIVETED W/HEX SCREW +HEX NUT

LOGO
 0=NO LOGO
 2=NEXTRON LOGO

INSULATOR COLOR
 0=BLACK
 6=BLUE
 9=WHITE


INSULATOR MATERIAL
 0=PBT
 2=NYLON

CONTACT PLATED:(CONTACT AREA)
 1=FULL GOLD 1u"
 2=GOLD 3u"
 3=GOLD 5u"
 4=GOLD 10u"
 5=GOLD 15u"
 6=GOLD 30u"

CONTACT MATERIAL
 2=BRASS

△ NUT POST HEIGHT(H)
 0=4.8mm(STD)
 1=4.8mm

37P	55.42	63.50	69.32	8.38	12.50
25P	38.96	47.04	53.04	8.38	12.50
15P	25.25	33.32	39.14	8.38	12.50
9P	16.92	24.99	30.81	8.38	12.50
POS NO.	A	B	C	D	E
	DIMENSION				



D	ECR-20049	△=1	2020/03/27
C	ECN-19105	△=1	2019/10/22
B	ECN-150091	UPDATE	2015/7/27
REV.	DESCRIPTION	DATE	ANGLES
			X°±3°

UNITS: ■ mm □ inch	SIZE A3	NAME: D-SUB DP TYPE MALE PCB SOLDER TYPE	NEXTRONICS ENGINEERING CORP.								
GENERAL TOLERANCE: (UNLESS SPECIFIED)		PART NO: Z-SUBDPXMXXXXXX	TITLE: CUSTOMER DWG								
4 PLACE	± **	± **	DWG NO: 010-0000-635								
3 PLACE	± **	± **	<table border="1"> <tr> <td>SCALE</td> <td>SHEET</td> <td>REV.</td> </tr> <tr> <td>1/1</td> <td>1/1</td> <td>D</td> </tr> </table>			SCALE	SHEET	REV.	1/1	1/1	D
SCALE	SHEET	REV.									
1/1	1/1	D									
2 PLACE	± 0.20	± **									
1 PLACE	± 0.30	± **									
DESIGN: Lu陳惠枝	2020/03/27										

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Nextronics](#) manufacturer:

Other Similar products are found below :

[Z-100083200100100](#) [Z-230011850209](#) [Z-B8103421000081](#) [Z-230011814209](#) [Z-S97311126S1BT01](#) [Z-230010826209W](#) [Z-S311024S1BT1A](#)
[Z-230011864209](#) [Z-SUBDBBF227A092](#) [Z-SUBHPFF507A022](#) [Z-211-1021-8021-001](#) [230-010-810-209](#) [230-011-830-209](#) [231-011-820-106](#)
[231-012-810-106](#) [231-012-840-106](#) [810-3410-012-4000](#) [Z-SUBDBAF107A090](#) [Z-211-0311-0021-001](#) [Z-81050100121000](#) [Z-](#)
[SUBDREF607A002](#) [Z-81014100114000](#) [230-011-820-209](#) [231-011-816-106](#) [Z-100163200100100](#) [100-083-200-1001-00](#) [Z-231011816106](#)
[Z-81026100114000](#) [Z-81064100114000](#) [Z-B8101021000081](#) [Z-S5224267B0000](#) [230-011-810-209](#) [231-011-810-106](#) [100-143-200-1001-00](#)
[Z-81010100134000](#) [Z-S11F0207B15000](#) [Z-81030100111000](#) [Z-81016100121000](#) [Z-SUBB0B0002QH82](#) [231-011-814-106](#) [810-1410-012-](#)
[4000](#) [213-8011-0021-001](#) [SUB-B0A0-002Q-H82](#) [Z-81014100134000](#) [100-183-100-1001-00](#) [SUB-B0C0-002Q-H82](#) [100-283-100-1001-00](#) [Z-](#)
[SUBHBFM102A022](#) [Z-SUBHBBF107A000](#) [100-326-100-1001-00](#)