HERMAPHRODITIC CONNECTORS WITH GOLD PLATING

TE Connectivity (TE) introduces the standard Hermaphroditic Blade and Receptacle connectors with selective gold plating. The gold plated connectors are suitable for harsh environments where moisture and high vibration may be present. The Wire-to-Board connectors are also available that accept select gold-plated contacts and mates to the new part number series of the surface mount Hermaphroditic Blade and Receptacle board to board connectors. The connector provides power to the first LED printed circuit board and between adjacent LED printed circuit boards in a linear lighting fixture.



Applications

- LED lighting modules
- LED lighting strips
- Channel lettering
- Commercial refrigeration LED lighting
- · Rail, bus and airplane LED lighting

Electrical

• Operating Current: 6 AMPS

• Operating Voltage: 125VAC/125VDC

• Dielectric Withstanding

Voltage: 1500VAC

Mechanical

• Operating Temperature: $-40^{\circ}\text{C} \text{ to } +105^{\circ}\text{C}$

• Mating cycles: 10

Product Specifications

• Product Specification: 108-2342 for

Hermaphroditic Products

• Application Specification: 114-13225 for Hermaphroditic

Board-to-Board Products

• Application Specification: 114-13252 for Hermaphroditic

Wire-to-Board Products

Materials

• Housing: UL 94V0 high temperature

resistant thermoplastic

• Contact: Gold over Nickel at separable

interface (tin over Nickel for the remainder)

Key Benefits

- Available in 2, 4 and 6 positions to connect power, signal and data
- Board to board connectors mate to themselves vertically and horizontally to simplify assembly and service
- Wire to board connectors provide positive latching
- Low profile, flat design with rounded corners eliminate shadowing
- Tape and reel packaged product is compatible with high speed SMT and reflow solder process
- Select gold plating eliminates the potential for fretting corrosion caused by micro motion in harsh LED lighting environments



Product Selection Information

BOARD-TO-BOARD PRODUCTS

	Housing Features	Positions	Housing Color	TE Part Number
real S	Standard	2	Natural	<u>2213613-1</u>
			Black	<u>1-2213613-1</u>
		4	Natural	2213613-2
			Black	1-2213613-2
		6	Natural	2213613-3
			Black	<u>1-2213613-3</u>
	with Single Latch	2	Natural	<u>2213614-1</u>
# 15±100			Black	<u>1-2213614-1</u>
7000 35		4	Natural	2213614-2
			Black	1-2213614-2
		6	Natural	2213614-3
			Black	<u>1-2213614-3</u>
812.1.38 Marie 113	with Dual Latch	2	Natural	<u>2213877-1</u>
R. C.			Black	1- 2213877-1
	with Post	2	Natural	<u>2213616-1</u>
953.1 us			Black	<u>1-2213616-1</u>
The second second		4	Natural	2213616-2
			Black	1-2213616-2
		6	Natural	2213616-3
			Black	<u>1-2213616-3</u>
ASSEMBLE OF THE PROPERTY OF TH	with Latch and Post	2	Natural	<u>2213617-1</u>
			Black	<u>1-2213617-1</u>
		4	Natural	2213617-2
			Black	1-2213617-2
		6	Natural	2213617-3
			Black	1-2213617-3

WIRE-TO-BOARD

Contact Style	TE Part Number	
Wire-to-Board Socket Contact, Select-Gold	<u>2213373-1</u>	
Wire-to-Board Blade Contact, Select-Gold	<u>2213374-1</u>	

Housing Features	Positions	Housing Color	TE Part Number
with Single Latch	2	Natural	<u>2058299-1</u>
		Black	<u>1-2058299-1</u>
	4	Natural	2058299-2
		Black	1-2058299-2
	6	Natural	2058299-3
		Black	<u>1-2058299-3</u>
with Dual Latch	2	Natural	<u>2213709-1</u>
		Black	1-2213709-1



Dimensions 7.10 [0.280] TYP 1.00 2.00±0.10 [0.079±0.003] TYP Ø0.800^{+0.050} 2.00±0.10 [0.079±0.003] TYP [0.0315+0.0019] 12.25 [0.482] TYP 4.75 [0.187] REF 1.50±0.10 [0.059±0.003] 3.50±0.08 [0.138±0.003] · 1.95 [0.077] REF 7.10 [0.280] 2 Position 4 Position 6 Position 4.00 [0.157] REF . 8.70 [0.343] 0.10 ш 0.13 [.005] MAX PERMISSIBLE MISALIGNMENT BETWEEN BOARD EDGE AND CONNECTOR FACE 1.95 [0.077] [0.077] [0.075] REF CENTER OF GRAVITY 0.80 [0.032] REF - 1.00 [0.039] 4.13 [0.163] ₿ 2 Position 4 Position 6 Position 24.70 [0:972] 1.60 [0.063] REF 16.50 [0.650] 15.50 [0.610] 鬈 20.40 [0.803] DIM A 12.40 [0.488] 28.40 [1.118] 0.05 ΗВ 髻 Z 霆 2 Position 4 Position 6 Position I.00 [0.039] TYP 19.50 w.Wo 2 Position

te.com

© 2016 TE Connectivity Ltd. Family of Companies. All Rights Reserved. TE, TE Connectivity, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and Company names mentioned herein may be trademarks of their respective owners. 1-1773878-4 JN 4/2016

USA: +1 (800) 522-6752 Canada: +1 (905) 475-6222 Mexico: +52 (0) 55-1106-0800 Latin/S. America: +54 (0) 11-4733-2200 Germany: +49 (0) 6251-133-1999 UK: +44 (0) 800-267666 France: +33 (0) 1-3420-8686 The Netherlands: +31 (0) 73-6246-999 China: +86 (0) 400-820-6015



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Lighting Connectors category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

21061-9 293300-7 2106117-2 293660-5 293700-2 CNX_H03_NTP 30-9767-BU 3-21030-1 ZCH-110-RGB-I 503471-0290 ES5P09K4F2

CNXH02NTP ZCH-110-RGB-J 217-0716-200 192992-0057 1954563-1 217-3030-000 217-3032-000 237-0734-003 DTS24W25-20PN-LC

1-2213614-2 2834049-3 ES9S002SZZ 2834049-2 2-2834067-3 1-293657-2 2834049-1 293699-2 293701-3 1-2213614-3 2834036-1

2834037-1 2213614-3 2307526-2 2-2106124-3 2-2834068-3 FLS2SC4001BP FLSC80352000 FLSC80354000 FLSC80353000 FLSSB8002

FLSSB8001 FLSC80351000 FLSC80355000 FLSSB4001 FLSC80504000 FLSC80502000 FLSC80501000 FLSC805050000