

SR3100L

SUPER LOW VF SCHOTTKY RECTIFIERS



VOLTAGE: 100 Volts CURRENT: 3 Amperes DO-27(DO-201AD) Marking and Polarity

FEATURES


- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Softest, fast switching capability
- Low Forward Voltage Drop
- High temperature soldering guaranteed:260 C/10 seconds at terminals
- Lead Free Finish, RoHS Compliant

MECHANICAL DATA

- **Case:** JEDEC DO-201AD molded plastic body
- **Terminals:** Plated axial leads, solderable per MIL-STD-750,method 2026
- **Mounting Position:** Any
- **Weight:**App. 1.05 grams (0.0353 ounce)

TYPICAL APPLICATIONS

- Device optimized for low forward voltage drop to maximize efficiency in Power Supply applications



Remark:

- ①. SR3100L=Model No.
- ②. NH=niuhang trademark
- ③. FFDDK=Internal control code,According to actual changes
- ④. White band denotes cathode

Maximum Ratings (Ratings at 25°C ambient temperature unless otherwise specified.)

| Parameter | Symbol | SR3100L | Unit |
|---|-------------|---------|------|
| Maximum repetitive peak reverse voltage | V_{RRM} | 100 | V |
| Maximum RMS voltage | V_{RMS} | 70 | V |
| Maximum DC blocking voltage | V_{DC} | 100 | V |
| Maximum average forward rectified current(see fig.1) | $I_{F(AV)}$ | 3 | A |
| Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method at rated TL)(see fig.5) | I_{FSM} | 125 | A |

Electrical Characteristics (Ratings at 25°C ambient temperature unless otherwise specified.)

| Parameter | Test Conditions | | Symbol | SR3100L | | | Unit |
|--|-------------------|---------------------------------------|--------|---------|------|------|---------|
| | | | | Min. | Typ. | Max. | |
| Maximum instantaneous forward voltage(see fig.2)(Note 1) | $T_A=25^\circ C$ | $I_F= 3 \text{ A}$ | V_F | -- | 0.71 | 0.80 | V |
| | $T_A=125^\circ C$ | | | -- | 0.66 | 0.74 | |
| Maximum instantaneous reversecurrent at rated DC blockingvoltage (see fig.3)(Note 1) | $T_A=25^\circ C$ | $V_R= V_{RRM}$ $V_R= 80\%*V_{RRM}$ | I_R | -- | 5 | 100 | μA |
| | $T_A=125^\circ C$ | | | -- | -- | 20 | mA |
| Typical junction capacitance(see fig.4) | 4V,1MHz | | C_J | -- | 160 | -- | pF |

Thermal Characteristcs (Ratings at 25°C ambient temperature unless otherwise specified)

| Parameter | Symbol | SR3100L | Unit |
|-------------------------------------|-----------------|------------|------|
| Operating junction | T_J | -55 to 150 | °C |
| Storage temperature range | T_{STG} | -55 to 150 | |
| Typical thermal resistance (Note 2) | $R_{\theta JA}$ | 25 | °C/W |
| | $R_{\theta JL}$ | 8 | |

- Note:
1. Pulse width < 300 μS , Duty cycle < 2%
 2. Thermal resistance from junction to lead vertical P.C.B. mounted , 0.375"(9.5mm)lead length,Polymide PCB, 2 oz Copper.

SR3100L

SUPER LOW VF SCHOTTKY RECTIFIERS



RATING AND CHARACTERISTIC CURVES




Fig.1- FORWARD CURRENT DERATING CURVE




Fig.2-TYPICAL INSTANTANEOUS FORWARD




Fig.3-TYPICAL REVERSE CHARACTERISTICS




Fig.4- TYPICAL JUNCTION CAPACITANCE




Fig.5-MAX. NON-REPETITIVE SURGE CURRENT




FIG.6-TYPICAL TRANSIENT THERMAL IMPEDANCE


SR3100L

SUPER LOW VF SCHOTTKY RECTIFIERS



OUTLINE DRAWINGS

DO-27(DO-201AD)



OUTLINE DIMENSIONS

| Dim. | Millimeters | | | Inches | | |
|------|-------------|------|------|--------|------|-------|
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 4.9 | - | 5.6 | 0.193 | - | 0.220 |
| B | 24.5 | - | 26.4 | 0.965 | - | 1.039 |
| C | 0.9 | - | 1.3 | 0.035 | - | 0.051 |
| D | 7.2 | - | 9.5 | 0.285 | - | 0.374 |

Packing Information

| Package | Pack | Box Size LxWxH(mm) | Quantity (pcs/box) | Carton Size LxWxH(mm) | Quantity (pcs/carton) |
|-----------------|------|-----------------------|-----------------------|--------------------------|--------------------------|
| DO-27(DO-201AD) | B/G | 255*75*140 | 1250 | 410*280*330 | 12500 |

SR3100L


SUPER LOW VF SCHOTTKY RECTIFIERS



Recommended wave soldering condition

| | | |
|-----------------|------------------|-----------------|
| Product | Peak Temperature | Soldering Time |
| Pb-free devices | 260 +0/-5 °C | 5 +1/-1 seconds |

Recommended temperature profile for IR reflow



| Profile feature | Sn-Pb eutectic Assembly | Pb-free Assembly |
|--|----------------------------------|----------------------------------|
| Average ramp-up rate (Tsmmax to Tp) | 3°C/second max. | 3°C/second max. |
| Preheat -Temperature Min(TS min) -Temperature Max(TS max) -Time(ts min to ts max) | 100°C 150°C 60-120 seconds | 150°C 200°C 60-180 seconds |
| Time maintained above: -Temperature (TL) - Time (tL) | 183°C 60-150 seconds | 217°C 60-150 seconds |
| Peak Temperature(TP) | 240 +0/-5 °C | 260 +0/-5 °C |
| Time within 5°C of actual peak temperature(tp) | 10-30 seconds | 20-40 seconds |
| Ramp down rate | 6°C/second max. | 6°C/second max. |
| Time 25 °C to peak temperature | 6 minutes max. | 8 minutes max. |

Note : All temperatures refer to topside of the package, measured on the package body surface.

SR3100L

SUPER LOW VF SCHOTTKY RECTIFIERS



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from niuhang Electronics co., LTD
- Niuhan Electronics co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhan Electronics co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhan Electronics co., LTD. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Niuhan Electronics co., LTD. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Niuhan Electronics co., LTD. for any damages resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to product the customer quality, change the internal structure and the production process Niuhan can not notify

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Schottky Diodes & Rectifiers](#) category:

Click to view products by [NH manufacturer](#):

Other Similar products are found below :

[MA4E2039](#) [MMBD301M3T5G](#) [RB160M-50TR](#) [D83C](#) [BAS16E6433HTMA1](#) [BAS 3010S-02LRH E6327](#) [BAT 54-02LRH E6327](#)
[NRVBAF360T3G](#) [NSR05F40QNXT5G](#) [NTE555](#) [JANS1N6640](#) [SS3003CH-TL-E](#) [GA01SHT18](#) [CRS10I30A\(TE85L,QM](#) [MBRA140TRPBF](#)
[MBRB30H30CT-1G](#) [BAT 15-04R E6152](#) [JANTX1N5712-1](#) [DMJ3940-000](#) [SB007-03C-TB-E](#) [NRVBB20100CTT4G](#) [NRVBM120LT1G](#)
[NTSB30U100CT-1G](#) [CRG04\(T5L,TEMQ\)](#) [ACDBA1100LR-HF](#) [ACDBA1200-HF](#) [ACDBA240-HF](#) [ACDBA3100-HF](#) [CDBQC0530L-HF](#)
[ACDBA260LR-HF](#) [ACDBA1100-HF](#) [10BQ015-M3/5BT](#) [NRVBM120ET1G](#) [VSSB410S-M3/5BT](#) [1N5819T-G](#) [PDS1040Q-13](#) [B160BQ-13-F](#)
[SDM05U20CSP-7](#) [BAS 70-07 E6433](#) [B140S1F-7](#) [HSM560Je3/TR13](#) [DDB2265-000](#) [ZHCS506QTA](#) [HSM190Je3/TR13](#) [B330AF-13](#)
[ACDBUC0230-HF](#) [SDM1U100S1F-7](#) [MBR10200CTF-G1](#) [CDLL5712](#) [DMF2822-000](#)