PLASTIC FILM CAPACITORS

Metallized Polyester Film Capacitor

(ZH) (Extended Standard Type)

- Highly reliable and superior performance in high frequency applications, self-healing and non-inductive construction, using a dielectric made of polyethylene terephthalate film covered with vacuum-evaporated metal.
- Finished by inner dipping with liquid epoxy resin and outer coating with flame-retardant epoxy resin, those double coating provides excellent humidity resistance.
- Designed to be compact and to cover larger capacitance range having advantage of tolerating to A.C.voltage and large current flow.
- Designed 1mm max. of epoxy on lead wire for best performance at soldering process on P.C. board assemblies.
- Compliant to the RoHS directive (2011/65/EU,(EU)2015/863).

Applications

- Filtering, DC-blocking, coupling and so on of general communications equipment and use in AC circuits for motor starting, charging / discharging, lighting, noise suppression and etc. Contact us for details for use in AC circuits.
- However, do not use this product for across-the-line applications.

Specifications


Item	Performance Characteristics						
Category Temperature Range	-40 to +105°C (Rated temperature : 85°C)						
Rated Voltage (U _R)	250, 400, 630VDC						
Rated Capacitance Range	0.01 to 3.3µF						
Rated Capacitance Tolerance	±5% (J), ±10% (K)						
Dielectric Loss Tangent	0.8% or less (at 1kHz 20°C)						
Insulation Resistance	$\label{eq:constraint} C \leqq 0.33 \mu F : 9000 \ \text{M}\Omega \ \text{or more} C > 0.33 \mu F : 3000 \ \Omega F \ \text{or more}$						
Withstand Voltage	Between Terminals : Rated Voltage × 175%, 1 to 5 secs. Between Terminals and Coverage : Rated Voltage × 200%, 1 to 5 secs.						
Encapsulation	Flame-retardant epoxy resin						

Category voltage = UR × 0.7

tation 10 K 400 P

nichicon

Type numbering system (Example : 630V 0.01µF)




AC Voltage


 AC voltage (Operating at 50 / 60Hz AC circuit) shall be as follows. However, do not use this product for across-the-line applications.

·····, -· ··· ··· ··· ··· ··· ··· ··· ··										
DC Rated Voltage	250VDC	400VDC	630VDC							
AC Voltage	125VAC	200VAC	250VAC							

 When used in high frequency circuit, refer to Table 2 and 3 in pages 399, 402 for the values of effective voltage, current and effective VA.



Drawing



Cut / formed lead type.

Dimensions

Dimensions Unit : mn													nit : mm						
V(Code) 250VDC (2E)						400VDC (2G)					630VDC (2J)								
Cap.(µF) Co	de Size	Т	W	Н	d	Р	F	Т	W	Н	d	Р	F	Т	W	Н	d	Р	F
0.01	103													4.8	15.5	9.4	0.6	12.5	12.5
0.015	153													5.5	15.5	10.0	0.6	12.5	12.5
0.022	223							4.9	13.5	9.5	0.6	10.5	10.0	6.3	15.5	10.8	0.6	12.5	12.5
0.033	333							5.6	13.5	10.2	0.6	10.5	10.0	7.1	15.5	12.3	0.6	12.5	12.5
0.047	473	4.7	13.5	9.3	0.6	10.5	10.0	5.5	15.5	10.1	0.6	12.5	12.5	6.2	20.5	11.5	0.6	17.5	17.5
0.068	683	4.7	13.5	9.3	0.6	10.5	10.0	6.3	15.5	10.9	0.6	12.5	12.5	6.7	20.5	13.5	0.6	17.5	17.5
0.1	104	5.3	13.5	9.9	0.6	10.5	10.0	7.3	15.5	11.9	0.6	12.5	12.5	7.8	20.5	14.6	0.6	17.5	17.5
0.15	154	5.5	15.5	10.1	0.6	12.5	12.5	6.6	20.5	11.8	0.6	17.5	17.5	8.0	26.0	15.3	0.8	22.5	22.5
0.22	224	6.3	15.5	10.9	0.6	12.5	12.5	7.7	20.5	12.9	0.6	17.5	17.5	8.9	26.0	17.6	0.8	22.5	22.5
0.33	334	7.4	15.5	12.0	0.6	12.5	12.5	8.6	20.5	15.3	0.6	17.5	17.5	10.9	26.0	19.8	0.8	22.5	22.5
0.47	474	6.7	20.5	11.9	0.6	17.5	17.5	10.1	20.5	16.9	0.6	17.5	17.5	11.3	31.0	20.2	0.8	27.5	27.5
0.68	684	7.2	20.5	14.0	0.6	17.5	17.5	9.5	26.0	18.4	0.8	22.5	22.5						
1.0	105	8.6	20.5	15.3	0.6	17.5	17.5	11.5	26.0	20.4	0.8	22.5	22.5						
1.5	155	8.3	26.0	17.1	0.8	22.5	22.5	12.3	31.0	21.1	0.8	27.5	27.5						
2.2	225	10.0	26.0	18.8	0.8	22.5	22.5												
3.3	335	10.7	31.0	19.6	0.8	27.5	27.5												

F : lead pitch for cut / formed lead wires



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Film Capacitors category:

Click to view products by Nichicon manufacturer:

Other Similar products are found below :

 F339X134748MIP2T0
 F450KG153J250ALH0J
 750-1018
 FKP1-1500160010P15
 FKP1R031007D00JYSD
 FKP1R031507E00JYSD

 FKP1U024707E00KYSD
 82DC4100CK60J
 82EC1100DQ50K
 PFR5101J100J11L16.5TA18
 PME261JB5220KR19T0
 A451GK223M040A

 A561ED221M450A
 QXJ2E474KTPT
 QXL2B333KTPT
 R49AN347000A1K
 EEC2G505HQA406
 B25668A6676A375
 B25673A4282E140

 BFC233868148
 BFC2370GC222
 C3B2AD44400B20K
 C4ASWBU3220A3EK
 CB027C0473J- CB17710184J- CB182K0184J- 23PW210

 950CQW5H-F
 SBDC3470AA10J
 SCD105K122A3-22
 2N3155
 A571EH331M450A
 FKP1-2202KV5P15
 FKS3-680040010P10

 QXL2E473KTPT
 445450-1
 B25669A3996J375
 46KI322000M1M
 46KR415050M1K
 4BSNBX4100ZBFJ
 MKP383510063JKP2T0

 MKPY2-.02230020P15
 MKT 1813-368-015
 4055292001
 46KN410000N1K
 EEC2E106HQA405
 EEC2G205HQA402
 EEC2G805HQA415

 P409CP224M250AH470
 82EC2150DQ50K
 A6KN410000N1K
 EEC2E106HQA405
 EEC2G205HQA402
 EEC2G805HQA415