

# **ALUMINUM ELECTROLYTIC CAPACITORS**



- Lower impedance than HD,HC series.
- Compliant to the RoHS directive (2002/95/EC).

Products which are scheduled to be discontinued. Not recommended for new designs






#### ■Specifications

| ltem                                  | Performance Characteristics   |               |      |  |      |  |  |  |
|---------------------------------------|---|---------------|------|--|------|--|--|--|
| Category Temperature Range            | -40 to +105°C   |               |      |  |      |  |  |  |
| Rated Voltage Range                   | 6.3 to 16V  |               |      |  |      |  |  |  |
| Rated Capacitance Range               | 330 to 12000μF  |               |      |  |      |  |  |  |
| Capacitance Tolerance                 | ±20% (120Hz, 20°C)  |               |      |  |      |  |  |  |
| Leakage Current                       | After 2 minutes' application of rated voltage, leakage current is less than 0.03CV  |               |      |  |      |  |  |  |
| Tananat at lana anala                 | For capacitance of more than 1000μF, add 0.02 for every increase of 1000μF  |               |      |  |      |  |  |  |
| Tangent of loss angle (tan $\delta$ ) | Rated voltage (V)   | 6.3           | 10   | 16                                       |      | 120Hz 20°C   |  |  |
|                                       | tan δ (MAX.)  | 0.22          | 0.19 | 1  | 0.16 |  |  |  |
| Stability at Low Temperature          | Rated voltage (V)   | 6.3           | 10   | 16                                       |      | 120Hz  |  |  |
|                                       | Impedance ratio ZT / Z20 (MAX.) Z—40°C / Z+20°C   | 3             | 3    |  | 3    |  |  |  |
| Endurance                             | The specifications listed at right shall be met when the capacitors are restored to 20°C after D.C. bias plus rated ripple current is applied for 2000 hours at 105°C, the peak voltage shall not exceed the rated voltage. |               |      | Capacitance change tan δ Leakage current |      | Within ±25% of the initial capacitance value 200% or less than the initial specified value Less than or equal to the initial specified value |  |  |
| Marking                               | Printed with white color letter on b  | olack sleeve. |      |  |      |  |  |  |

### ■Radial Lead Type




• Please refer to page 20 about the end seal configulation.



|   |   | (n  |     |      |     |     |  |
|---|---|-----|-----|------|-----|-----|--|
| ф | D | 8   | 10  | 12.5 | 16  | 18  |  |
|   | Р | 3.5 | 5.0 | 5.0  | 7.5 | 7.5 |  |
| ф | d | 0.6 | 0.6 | 0.6  | 0.8 | 0.8 |  |

## Type numbering system (Example: 6.3V 1800μF)



※ Configuration Pb-free leadwire Pb-free PET sleeve 8 · 10 PD 12.5 to 18 HD

#### ■Standard Ratings

| V (Code) |              |  | 6.3 (0J)                                |   |  | 10 (1A)                                 |   | 16 (1C)                                |   |   |  |
|----------|--------------|--|---|---|--|---|---|--|---|---|--|
| Cap.(μF) | Item<br>Code | Case size<br>$\phi D \times L$<br>(mm) | Impedance<br>(mΩ) MAX.<br>20°C / 100kHz | Rated ripple<br>(mArms)<br>105°C / 100kHz | Case size<br>$\phi D \times L$<br>(mm) | Impedance<br>(mΩ) MAX.<br>20°C / 100kHz | Rated ripple<br>(mArms)<br>105°C / 100kHz | Case size<br>$\phi D \times L$<br>(mm) | Impedance<br>(mΩ) MAX.<br>20°C / 100kHz | Rated ripple<br>(mArms)<br>105°C / 100kHz |  |
| 330      | 331          |  |   |   |  |   |   | 8 × 11.5                               | 30                                      | 1140                                      |  |
| 470      | 471          |  |   |   | 8 × 11.5                               | 30                                      | 1140                                      | 8 × 11.5                               | 30                                      | 1140                                      |  |
| 470      | 4/1          |  |   |   |  |   |   | ▲ 10 × 12.5                            | 25                                      | 1540                                      |  |
| 560      | 561          | 8 × 11.5                               | 30                                      | 1140                                      |  |   |   |  |   |   |  |
|          |              |  |   |   | 8 × 11.5                               | 30                                      | 1140                                      | 10 × 12.5                              | 25                                      | 1540                                      |  |
| 680      | 681          |  |   |   | ▲ 10 × 12.5                            | 25                                      | 1540                                      | ▲ 8×15                                 | 28                                      | 1490                                      |  |
| 000      | 001          |  |   |   |  |   |   | ● 8×20                                 | 18                                      | 1870                                      |  |
|          |              |  |   |   |  |   |   | ○10 ×16                                | 18                                      | 2000                                      |  |
| 820      | 821          | 8 × 11.5                               | 30                                      | 1140                                      |  |   |   |  |   |   |  |
|          |              | 8 × 15                                 | 28                                      | 1490                                      | 10 × 12.5                              | 25                                      | 1540                                      | 10 × 16                                | 18                                      | 2000                                      |  |
| 1000     | 102          | ▲10 ×12.5                              | 25                                      | 1540                                      | ▲ 8 × 15                               | 28                                      | 1490                                      | ▲ 8×20                                 | 18                                      | 1870                                      |  |
|          | 102          | ● 8 ×11.5                              | 30                                      | 1140                                      | ●10 ×16                                | 18                                      | 2000                                      | ● 10 × 20                              | 13                                      | 2550                                      |  |
|          |              |  |   |   | ○ 8 × 20                               | 18                                      | 1870                                      |  |   |   |  |
| 1200     | 122          | 8 × 15                                 | 28                                      | 1490                                      |  |   |   |  |   |   |  |
|          |              | 10 × 12.5                              | 25                                      | 1540                                      | 10 × 16                                | 18                                      | 2000                                      |  |   |   |  |
| 1500     | 152          | <u> </u>                               | 16                                      | 1950                                      | ▲ 8×20                                 | 18                                      | 1870                                      | 10 × 20                                | 13                                      | 2550                                      |  |
|          |              | ●10 ×16                                | 18                                      | 2000                                      |  |   |   |  |   |   |  |
| 4000     | 182          | 10 × 16                                | 19                                      | 2000                                      | 10 × 20                                | 13                                      | 2550                                      | 10 × 25                                | 12                                      | 2800                                      |  |
| 1800     | 102          | ▲ 8 × 20                               | 16                                      | 1950                                      | 10 × 20                                |   |   | <b>▲</b> 12.5 × 20                     | 11                                      | 2800                                      |  |
|          |              | 10 × 20                                | 13                                      | 2550                                      | 10 × 25                                | 12                                      | 2800                                      |  |   |   |  |
| 2200     | 222          | <u> </u>                               | 16                                      | 1950                                      |  |   |   |  |   |   |  |
|          |              | ●10 ×16                                | 18                                      | 2000                                      |  |   |   |  |   |   |  |
| 2700     | 272          | 10 × 20                                | 13                                      | 2550                                      | 12.5 × 20                              | 11                                      | 3000                                      | 12.5 × 25                              | 10                                      | 2900                                      |  |
| 3300     |              | 10 × 25                                | 12                                      | 2800                                      |  | 10                                      | 2900                                      |  |   |   |  |
|          | 332          | <b>▲</b> 12.5 × 20                     | 11                                      | 3000                                      | 12.5 × 25                              |   |   | 16 × 25                                | 9                                       | 3070                                      |  |
|          |              | ○10 × 20                               | 13                                      | 2550                                      |  |   |   |  |   |   |  |
| 5600     | 562          | 12.5 × 25                              | 10                                      | 2900                                      |  |   |   | 18 × 25                                | 8                                       | 3250                                      |  |
| 6800     | 682          |  |   |   | 16 × 25                                | 9                                       | 3070                                      |  |   |   |  |
| 8200     | 822          | 16 × 25                                | 9                                       | 3070                                      | 18 × 25                                | 8                                       | 3250                                      |  |   |   |  |
| 12000    | 123          | 18 × 25                                | 8                                       | 3250                                      |  |   |   |  |   |   |  |

Please refer to page 20, 21, 22 about the formed or taped product spec. Please refer to page 4 for the minimum order quantity.

- ▲: In this case, @will be put at 12th digit of type numbering system.
  •: In this case, @will be put at 12th digit of type numbering system.
- o: In this case, 9 will be put at 12th digit of type numbering system.

CAT.8100A-1

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Nichicon manufacturer:

Other Similar products are found below:

PCR1C681MCL1GS LAR2E821MELC30 LKS1V103MESB LKS1V332MESA LLS1E682MELZ LNC2G182MSEF LNC2G392MSEG
LNC2G472MSEH LNC2G682MSEG LNC2G682MSEH LNC2V272MSEG LNC2V332MSEG LNC2W682MSEH LNK2G122MSEF
LNK2G182MSEF LNK2V182MSEF LNK2V222MSEF LNR1V334MSE LNT1C105MSE LNT1E154MSE LNT1E474MSE LNT1J103MSE
LNT2E103MSE LNT2E222MSE LNT2G392MSEH LNT2H222MSEG LNT2H471MSEF LNU2G562MSEH LNUN7102MSEF
LNX2H122MSEG LNX2H182MSEG LNX2V273MSEK LNX2W222MSEH LNX2W272MSEH LNY2G222MSEF LNY2V682MSEG
LNY2W182MSEG LNY2W392MSEH LQR2G562MSEH LQR2W472MSEG POLYHC-KIT TVX1C220MAD UCA2W330MHD6
UFW1H332MHD UHE1E102MHD6 UHE1V102MHD1TO UHV1V102MHD UHW1E102MPD UKA1V332MHD UKL1H102MHD