



# ALUMINUM ELECTROLYTIC CAPACITORS

## WT series

Chip Type, Wide Temperature Range





- Chip type operating over wide temperature range of to  $-55$  to  $+105^{\circ}\text{C}$ .
- Designed for surface mounting on high density PC board.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU).



### Specifications


Item	Performance Characteristics							
Category Temperature Range	$-55$ to $+105^{\circ}\text{C}$							
Rated Voltage Range	4 to 50V							
Rated Capacitance Range	0.1 to $1500\mu\text{F}$							
Capacitance Tolerance	$\pm 20\%$ at 120Hz, $20^{\circ}\text{C}$							
Leakage Current	After 2 minutes' application of rated voltage, leakage current is not more than $0.01\text{CV}$ or $3(\mu\text{A})$ , whichever is greater.							
Tangent of loss angle (tan $\delta$ )	Measurement frequency : 120Hz at $20^{\circ}\text{C}$							
	Rated voltage (V)	4    6.3    10    16    25    35    50						
	tan $\delta$ (MAX.)	0.40    0.30    0.24    0.20    0.16    0.14    0.14						
Stability at Low Temperature	Measurement frequency : 120Hz							
	Rated voltage (V)	4    6.3    10    16    25    35    50						
	Impedance ratio	Z $-25^{\circ}\text{C}$ / Z $+20^{\circ}\text{C}$ 7    4    3    2    2    2    2						
	ZT / Z20 (MAX.)	Z $-40^{\circ}\text{C}$ / Z $+20^{\circ}\text{C}$ 15    8    8    4    4    3    3						
Endurance	The specifications listed at right shall be met when the capacitors are restored to $20^{\circ}\text{C}$ after the rated voltage is applied for 1000 hours at $105^{\circ}\text{C}$ .	<table border="1"> <tr> <td>Capacitance change</td> <td>Within <math>\pm 25\%</math> of the initial capacitance value for capacitors of <math>\phi 3\text{mm}</math> unit, and 16V or less. Within <math>\pm 20\%</math> of the initial capacitance value for capacitors of 25V or more.</td> </tr> <tr> <td>tan <math>\delta</math></td> <td>200% or less than the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>Less than or equal to the initial specified value</td> </tr> </table>	Capacitance change	Within $\pm 25\%$ of the initial capacitance value for capacitors of $\phi 3\text{mm}$ unit, and 16V or less. Within $\pm 20\%$ of the initial capacitance value for capacitors of 25V or more.	tan $\delta$	200% or less than the initial specified value	Leakage current	Less than or equal to the initial specified value
Capacitance change	Within $\pm 25\%$ of the initial capacitance value for capacitors of $\phi 3\text{mm}$ unit, and 16V or less. Within $\pm 20\%$ of the initial capacitance value for capacitors of 25V or more.							
tan $\delta$	200% or less than the initial specified value							
Leakage current	Less than or equal to the initial specified value							
Shelf Life	After storing the capacitors under no load at $105^{\circ}\text{C}$ for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at $20^{\circ}\text{C}$ , they shall meet the specified values for the endurance characteristics listed above.							
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at $250^{\circ}\text{C}$ . The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to $20^{\circ}\text{C}$ .	<table border="1"> <tr> <td>Capacitance change</td> <td>Within <math>\pm 10\%</math> of the initial capacitance value</td> </tr> <tr> <td>tan <math>\delta</math></td> <td>Less than or equal to the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>Less than or equal to the initial specified value</td> </tr> </table>	Capacitance change	Within $\pm 10\%$ of the initial capacitance value	tan $\delta$	Less than or equal to the initial specified value	Leakage current	Less than or equal to the initial specified value
Capacitance change	Within $\pm 10\%$ of the initial capacitance value							
tan $\delta$	Less than or equal to the initial specified value							
Leakage current	Less than or equal to the initial specified value							
Marking	Black print on the case top.							

### Chip Type



※1. Voltage mark for 6.3V is 「6V」. In case of marking for  $\phi 3$  units, "V" for rated voltage is omitted.  
 ※2. In case of marking for  $\phi 3$  units. Lot No is expressed by a digit (month code).

### Type numbering system (Example : 16V 10 $\mu\text{F}$ )



$\phi D \times L$	3 $\times$ 5.4	4 $\times$ 5.4	5 $\times$ 5.4	6.3 $\times$ 5.4	6.3 $\times$ 5.8	6.3 $\times$ 7.7	8 $\times$ 5.4	8 $\times$ 10	10 $\times$ 10
A	1.5	1.8	2.1	2.4	2.4	2.4	3.3	2.9	3.2
B	3.3	4.3	5.3	6.6	6.6	6.6	8.3	8.3	10.3
C	3.3	4.3	5.3	6.6	6.6	6.6	8.3	8.3	10.3
E	0.8	1.0	1.3	2.2	2.2	2.2	2.3	3.1	4.5
L	5.4	5.4	5.4	5.4	5.8	7.7	5.4	10	10
H	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.8 to 1.1	0.8 to 1.1

● Dimension table in next page.

## ■ Dimensions

Cap. (μF)	Code	V		4		6.3		10		16		25		35		50	
		0G	0J	1A	1C	1E	1V	1H									
0.1	0R1															4 × 5.4 (3)	1.0
0.22	R22															4 × 5.4 (3)	2.6
0.33	R33															4 × 5.4 (3)	3.2
0.47	R47															4 × 5.4 (3)	3.8
1	010															4 × 5.4 (3)	6.3(5.9)
2.2	2R2												3 × 5.4	7.5		4 × 5.4 (3)	11 (9)
3.3	3R3												3 × 5.4	9		4 × 5.4	14
4.7	4R7											4 × 5.4 (3)	13 (10)	4 × 5.4	15	5 × 5.4	19
10	100							4 × 5.4 (3)	18 (14)	5 × 5.4	23	5 × 5.4	25	6.3 × 5.4	30		
22	220	4 × 5.4	22	4 × 5.4	22	5 × 5.4	27	5 × 5.4	30	6.3 × 5.4	38	6.3 × 5.4	42	• 8 × 5.4	51 (45)		
33	330	5 × 5.4	30	5 × 5.4	30	5 × 5.4	35	6.3 × 5.4	40	6.3 × 5.4	48	• 8 × 5.4	59 (52)	6.3 × 7.7	60		
47	470	5 × 5.4	36	5 × 5.4	36	6.3 × 5.4	46	6.3 × 5.4	50	• 8 × 5.4	66 (59)	6.3 × 5.8	63	6.3 × 7.7	63		
100	101	6.3 × 5.4	60	6.3 × 5.4	60	6.3 × 5.4	60	6.3 × 5.4	60	6.3 × 7.7	91	6.3 × 7.7	84	8 × 10	140		
150	151	6.3 × 5.8	86	6.3 × 5.8	86	6.3 × 5.8	86	6.3 × 7.7	95	8 × 10	140	8 × 10	155	10 × 10	180		
220	221	• 8 × 5.4	102 (91)	• 8 × 5.4	102 (91)	6.3 × 7.7	105	6.3 × 7.7	105	8 × 10	155	8 × 10	190	10 × 10	220		
330	331	6.3 × 7.7	105	6.3 × 7.7	105	8 × 10	195	8 × 10	195	8 × 10	190	10 × 10	300				
470	471	8 × 10	210	8 × 10	210	8 × 10	210	8 × 10	230	10 × 10	300						
680	681	8 × 10	210	8 × 10	210	10 × 10	310	10 × 10	310								
1000	102	8 × 10	230	8 × 10	230	10 × 10	310										Case size
1500	152	10 × 10	310	10 × 10	310												φ D × L (mm)

Rated ripple current (mArms) at 105°C 120Hz

( ) is also available with φ3mm upon request. In such a case, [2] will be put at 12th digit of type numbering system.

Size φ6.3 × 5.8 is available for capacitors marked. " • " In such a case, [6] will be put at 12th digit of type numbering system.

## ● Frequency coefficient of rated ripple current

Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz or more
Coefficient	0.70	1.00	1.17	1.36	1.50

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please select UX(p.154), UJ(p.160) series if high C/V products are required.
- Please refer to page 3 for the minimum order quantity.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Nichicon](#) manufacturer:*

Other Similar products are found below :

[PCR1C681MCL1GS](#) [LAR2E821MELC30](#) [LKS1V103MESB](#) [LKS1V332MESA](#) [LLS1E682MELZ](#) [LNC2G182MSEF](#) [LNC2G392MSEG](#)  
[LNC2G472MSEH](#) [LNC2G682MSEG](#) [LNC2G682MSEH](#) [LNC2V272MSEG](#) [LNC2V332MSEG](#) [LNC2W682MSEH](#) [LNK2G122MSEF](#)  
[LNK2G182MSEF](#) [LNK2V182MSEF](#) [LNK2V222MSEF](#) [LNR1V334MSE](#) [LNT1C105MSE](#) [LNT1E154MSE](#) [LNT1E474MSE](#) [LNT1J103MSE](#)  
[LNT2E103MSE](#) [LNT2E222MSE](#) [LNT2G392MSEH](#) [LNT2H222MSEG](#) [LNT2H471MSEF](#) [LNU2G562MSEH](#) [LNUN7102MSEF](#)  
[LNX2H122MSEG](#) [LNX2H182MSEG](#) [LNX2V273MSEK](#) [LNX2W222MSEH](#) [LNX2W272MSEH](#) [LNY2G222MSEF](#) [LNY2V682MSEG](#)  
[LNY2W182MSEG](#) [LNY2W392MSEH](#) [LQR2G562MSEH](#) [LQR2W472MSEG](#) [POLYHC-KIT](#) [TVX1C220MAD](#) [UCA2W330MHD6](#)  
[UFW1H332MHD](#) [UHE1E102MHD6](#) [UHE1V102MHD1TO](#) [UHV1V102MHD](#) [UHW1E102MPD](#) [UKA1V332MHD](#) [UKL1H102MHD](#)