





**PRODUCT SUMMARY**

$V_{(BR)DSS}$	$R_{DS(ON)}$	$I_D$
30V	20mΩ	5A



- 1. GATE
- 2. DRAIN
- 3. SOURCE

**ABSOLUTE MAXIMUM RATINGS ( $T_A = 25\text{ °C}$  Unless Otherwise Noted)**

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		$V_{DS}$	30	V
Gate-Source Voltage		$V_{GS}$	±20	V
Continuous Drain Current	$T_A = 25\text{ °C}$	$I_D$	5	A
	$T_A = 70\text{ °C}$		3.7	
Pulsed Drain Current <sup>1</sup>		$I_{DM}$	15	
Power Dissipation	$T_A = 25\text{ °C}$	$P_D$	0.8	
	$T_A = 70\text{ °C}$		0.5	
Operating Junction & Storage Temperature Range		$T_j, T_{stg}$	-55 to 150	°C

**THERMAL RESISTANCE RATINGS**

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Ambient <sup>2</sup>	$R_{\theta JA}$		146	°C / W
Junction-to-Case	$R_{\theta JC}$		60	

<sup>1</sup>Pulse width limited by maximum junction temperature.

<sup>2</sup>The value of  $R_{\theta JA}$  is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A = 25\text{ °C}$ .

**ELECTRICAL CHARACTERISTICS ( $T_J = 25\text{ °C}$ , Unless Otherwise Noted)**


PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
<b>STATIC</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	30			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	1.3	1.75	2.3	
Gate-Body Leakage	$I_{GSS}$	$V_{DS} = 0V, V_{GS} = \pm 20V$			±100	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 24V, V_{GS} = 0V$			1	μA
		$V_{DS} = 20V, V_{GS} = 0V, T_J = 55\text{ °C}$			10	
Drain-Source On-State Resistance <sup>1</sup>	$R_{DS(ON)}$	$V_{GS} = 4.5V, I_D = 5A$		23	31	mΩ
		$V_{GS} = 10V, I_D = 5A$		17	20	

Forward Transconductance <sup>1</sup>	$g_{fs}$	$V_{DS} = 5V, I_D = 5A$		26		S
<b>DYNAMIC</b>						
Input Capacitance	$C_{iss}$	$V_{GS} = 0V, V_{DS} = 15V, f = 1MHz$		329		pF
Output Capacitance	$C_{oss}$			70		
Reverse Transfer Capacitance	$C_{rss}$			45		
Total Gate Charge <sup>2</sup>	$Q_g$	$V_{DS} = 15V, V_{GS} = 10V, I_D = 5A$		7.8		nC
Gate-Source Charge <sup>2</sup>	$Q_{gs}$			1.2		
Gate-Drain Charge <sup>2</sup>	$Q_{gd}$			2.3		
Turn-On Delay Time <sup>2</sup>	$t_{d(on)}$	$V_{DS} = 15V, I_D \cong 5A, V_{GS} = 10V, R_{GEN} = 6\Omega$		17		nS
Rise Time <sup>2</sup>	$t_r$			17		
Turn-Off Delay Time <sup>2</sup>	$t_{d(off)}$			37		
Fall Time <sup>2</sup>	$t_f$			18		
<b>SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T<sub>J</sub> = 25 °C)</b>						
Continuous Current	$I_S$				0.7	A
Forward Voltage <sup>1</sup>	$V_{SD}$	$I_F = 5A, V_{GS} = 0V$			1.1	V
Reverse Recovery Time	$t_{rr}$	$I_F = 5A, di_F/dt = 100A / \mu S$		10		nS
Reverse Recovery Charge	$Q_{rr}$			2.6		nC


<sup>1</sup>Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

<sup>2</sup>Independent of operating temperature.


**Output Characteristics**




**Transfer Characteristics**




**On-Resistance VS Temperature**




**Capacitance Characteristic**




**Gate charge Characteristics**




**Source-Drain Diode Forward Voltage**




**Safe Operating Area**



**Single Pulse Maximum Power Dissipation**



**Transient Thermal Response Curve**



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [NIKO](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)  
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)  
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)  
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)  
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)  
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)