

Specification:

1) Rating (if not described next to the switch):


3 A 125 VAC; 1 A 250 VAC

2) Contact Resistance: 20 mW max.

3) Insulation Resistance: 500 VDC 100 MW min.

4) Dielectric strength: 1000 VAC, 1 minute

5) Electrical Life: 50000 cycles



CIRCUITRY TRAIT

Α	ON - OFF	Push on/Push off	With lock	
В	OFF - (ON)	Push on	Momentary	
С	ON - (OFF)	Push off	Momentary	

() indicates momentary


PUSH BUTTON COLOUR

RD	red	
GN	green	
OR	orange	
BU	blue	
WH	white	
BK	black	
YL	yellow	

<u>Ninigi</u>




PS11A ON-OFF **PS11B** OFF-(ON) **PS11C** ON-(OFF)





PS12A ON-OFF **PS12B** OFF-(ON) **PS12C** ON-(OFF)






 PS14A
 ON-OFF


 PS14B
 OFF-(ON)

 PS14C
 ON-(OFF)







PS16A ON-OFF **PS16B** OFF-(ON) **PS16C** ON-(OFF)






PS13B OFF-(ON) **PS13C** ON-(OFF) 8 A 125 VAC; 4 A 250 VAC







PS10B OFF-(ON) (plastic rod)






<u>Ninigi</u>




PS10B2 OFF-(ON) PS10C2 ON-(OFF) (metal rod)








PS15A ON-OFF









PS15B OFF-(ON) **PS15C** ON-(OFF)











PS17A ON-OFF 4 A 125 VAC; 2 A 250 VAC











PS17A2 ON-OFF (PS17B)











PS17A3 ON-OFF (PBS-17B) 4 A 125 VAC; 2 A 250 VAC









Ninigi



PS19B OFF-(ON) **PS19C** ON-(OFF) 5 A 125 VAC; 2.5 A 250 VAC











PS19B2 OFF-(ON) **PS19C2** ON-(OFF) 5 A 125 VAC; 2.5 A 250 VAC











PS19B3 OFF-(ON) **PS19C3** ON-(OFF) 5 A 125 VAC; 2.5 A 250 VAC










PS20A ON-OFF PS20B OFF-(ON)








PS20A2 ON-OFF PS20B2 OFF-(ON)




t 0 13





PS21A ON-OFF PS21B OFF-(ON)






Ninigi




PS22A ON-OFF PS22B OFF-(ON)






PS23B OFF-(ON)






PS24B2 OFF-(ON) **PS24C2** ON-(OFF) 10 A 125 VAC; 2.5 A 250 VAC SPST 2P










PS24102 ON-ON **PS24112** ON-(ON) 4 A 125 VAC; 2 A 250 VAC SPDT 3P (L=14.2, 11.8, 9.8)











PS24202 ON-ON **PS24212** ON-(ON) 4 A 125 VAC; 2 A 250 VAC DPDT 6P (L=14.2, 11.8, 9.8)











PS24102P ON-ON **PS24112P** ON-(ON) 4 A 125 VAC; 2 A 250 VAC SPDT 3P (L=14.2, 11.8, 9.8)








<u> Ninigi</u>




PS24202P ON-ON **PS24212P** ON-(ON) 4 A 125 VAC; 2 A 250 VAC DPDT 6P (L=14.2, 11.8, 9.8)






PS26B OFF-(ON) **PS26C** ON-(OFF) 4 A 125 VAC; 2 A 250 VAC






PS27B OFF-(ON)






PS28B OFF-(ON) 4 A 125 VAC; 2 A 250 VAC






PS29B OFF-(ON)






PS30B OFF-(ON)



Ninigi




PS31B OFF-(ON)






PS32B OFF-(ON) 10 A 125 VAC; 6 A 250 VAC






PS33B OFF-(ON)






PS28B-2 OFF-(ON) 4 A 125 VAC; 2 A 250 VAC





PS28B-3 OFF-(ON) 4 A 125 VAC; 2 A 250 VAC



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by Ninigi manufacturer:

Other Similar products are found below:

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000

MDPSSGLFS 810KSV30B FLT 2U EE 01A MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL

8646ABUL FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL

ABD122N-B 1211390004 ABN111-Y ABN400-R 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047

1241.2511 1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6

1301940184 RELBARF6X10(PLASTIC)