


NOTE:

MATERIAL HOUSING:	NYLON 9T, UL94V-0, BLACK
CONTACT:	260°C PROCESS TEMP
SHELL:	PHOSPHOR BRONZE
BOARDLOCK:	NICKEL PLATED STEEL
INSERT/STANDOFF:	TIN PLATED STEEL
	NICKEL PLATED BRASS
FINISH	
CONTACT:	GOLD FLASH MATING AREA
	TIN PLATED SOLDER TAILS
ELECTRICAL	
RATED CURRENT:	2A
WORKING VOLTAGE:	250V
INSULATION RESISTANCE:	1 GΩhms MIN.
CONTACT RESISTANCE:	15 mΩhms MAX.
ENVIRONMENT	
OPERATION TEMPERATURE:	-55°C TO +105°C


193-015-213RYY1

53 = #4-40 INSERT WITH BOARD LOCKS
 56 = #4-40 STANDOFFS WITH BOARD LOCKS

OPTION "53"



OPTION "56"



RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
P. JENKINS

DATE:
09/15/2005

NorComp

SCALE:
NTS

SHEET OF
1 1

REV
4

DWG NO.

193-015-213RYY1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [D-Sub High Density Connectors](#) category:

Click to view products by [NorComp](#) manufacturer:

Other Similar products are found below :

[97-3250-11](#) [163A16809X](#) [163A17089X](#) [164A17199X](#) [242A25680X](#) [L717HDB44POL2R210](#) [L717HDEH15POL2](#) [L777HDE15P](#)
[L77HDE15SC309](#) [163A16759X](#) [163A16839X](#) [163A16989X](#) [163A17079X](#) [164A17329X](#) [164A18219X](#) [241A16440X](#) [241A16550X](#)
[241A16680X](#) [241A20810X](#) [241A25740X](#) [CT25-44P](#) [MDBE15PE766](#) [L177HDE15SOL2RM23](#) [L177HRC62S](#) [L177HRC62SVFM](#)
[L177HRCG62S](#) [L717HDEG15POL2RM5](#) [L77HDA26SVF](#) [L77HDE15SD1CO](#) [L77HDEH15SOL2RM832](#) [443895-3](#) [106698-1](#) [280-012K2C](#)
[L177HRB44S](#) [164A17039X](#) [09562004701510](#) [164A17969X](#) [L777HRC62P](#) [241A17960X](#) [164A18269X](#) [280-019S1S9MEN](#) [L777HDEG15P](#)
[280-018P3S25MEGN](#) [206504-2](#) [40-9515HDSP](#) [2057140-1](#) [C115370-6002](#) [DFMA104SNMBFR172FR022](#) [HDC9F200E2S](#)
[L717HDAG26POL2RM8](#)