
DESCRIPTION: M12 FEMALE - PANEL MOUNT (REAR) - 8 POS. - X-CODE - ROTATED



NOTE: MATERIAL HOUSING: PA66 UL94V-0, BLACK CONTACT: **BRASS** NUT: **BRASS** SHELL: **BRASS** □-RING: EPDM, BLACK ZINC ALLOY X-SHELL: **FINISH** CONTACT: GOLD 104" MIN. □VER 504" NICKEL NUT: NICKEL PLATED SHELL: NICKEL PLATED X-SHELL: NICKEL PLATED **ELECTRICAL** RATED CURRENT: 0.5A RATED VOLTAGE: 50VAC/60VDC INSULATION RESISTANCE: 100 MOhms MIN. CONTACT RESISTANCE: 10 mDhms MAX. WATER PROOF: IP67 **ENVIRONMENT OPERATION TEMPERATURE:** -40°C TD +85°C MAX WIRE AWG: 24

## 859-X08-203R0RY

4 = 10u″ GOLD

ROHS COMPLIANT

区

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

J. KADEL

DATE:

05/02/2019

UNITS = mm

## DO NOT SCALE FROM DRAWING



SCALE:	SHEET	OF		REV
NTS	1		1	2
DWG NO.	359-X0	)8-20	D3R0RY	

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by NorComp manufacturer:

Other Similar products are found below:

600X518037X MA1EAF1200 6STD15PCR99B70A 8R4000A16M020 8R4A00A18M020 8R5000A16M005 1200910008 1200910011 1300140094 130203-0054 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-01016 41-40011 41-40017 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00002 43-01166 41-40005 41-40016 43-00161 43-01191 XS3P-M421-2 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R4006A16A120 8R4000A16M010 RKC 50/16 1R3004A20A1201 6-22279-3 N03FA03144 1300140077 XS8A-0441 859RD04-103R004 860RD04-213R004 860RD04-213R004 860-X08-213R004 1-213245-2 2273142-2