



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089

NTE2407 Silicon PNP Transistor General Purpose Amp, Surface Mount (Compl to NTE2406)

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Collector–Base Voltage, V_{CBO}	60V
Collector–Emitter Voltage, V_{CEO}	60V
Emitter–Base Voltage, V_{EBO}	5V
Continuous Collector Current, I_C	600mA
Total Device Dissipation (FR–5 Board, Note 1), P_D	225mW
Derate above $+25^\circ\text{C}$	1.8mW/ $^\circ\text{C}$
Thermal Resistance, Junction–to–Ambient (FR–5 Board, Note 1), R_{thJA}	556 $^\circ\text{C}/\text{W}$
Total Device Dissipation (Alumina Substrate, Note 2), P_D	300mW
Derate above $+25^\circ\text{C}$	2.4mW/ $^\circ\text{C}$
Thermal Resistance, Junction–to–Ambient (Alumina Substrate, Note 2), R_{thJA}	417 $^\circ\text{C}/\text{W}$
Operating Junction Temperature Range, T_J	-55° to $+150^\circ\text{C}$
Storage Temperature Range, T_{stg}	-55° to $+150^\circ\text{C}$

Note 1. FR–5 = 1.000 (25.4mm) x .750 (19.05mm) x .062 (1.57mm).

Note 2. Alumina = .400 (10.2mm) x .300 (7.62mm) x .024 (.609mm), 99.5% alumina.

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
OFF Characteristics						
Collector–Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10\mu\text{A}, I_E = 0$	60	–	–	V
Collector–Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 10\text{mA}, I_B = 0$, Note 3	60	–	–	V
Emitter–Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10\mu\text{A}, I_C = 0$	5	–	–	V
Collector Cutoff Current	I_{CBO}	$V_{CB} = 50\text{V}, I_E = 0$	–	–	0.01	μA
		$V_{CB} = 50\text{V}, I_E = 0, T_A = +125^\circ\text{C}$	–	–	10	μA
	I_{CEX}	$V_{CE} = 30\text{V}, V_{EB(off)} = 0.5\text{V}$	–	–	50	nA
Base Current	I_B	$V_{CE} = 30\text{V}, V_{EB(off)} = 0.5\text{V}$	–	–	50	nA

Note 3. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
ON Characteristics (Note 3)						
DC Current Gain	h_{FE}	$V_{CE} = 10\text{V}, I_C = 0.1\text{mA}$	35	–	–	
		$V_{CE} = 10\text{V}, I_C = 1\text{mA}$	50	–	–	
		$V_{CE} = 10\text{V}, I_C = 10\text{mA}$	100	–	–	
		$V_{CE} = 10\text{V}, I_C = 150\text{mA}$	100	–	300	
		$V_{CE} = 10\text{V}, I_C = 500\text{mA}$	50	–	–	
Collector–Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 150\text{mA}, I_B = 15\text{mA}$	–	–	0.4	V
		$I_C = 500\text{mA}, I_B = 50\text{mA}$	–	–	1.6	V
Base–Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 150\text{mA}, I_B = 15\text{mA}$	–	–	1.3	V
		$I_C = 500\text{mA}, I_B = 50\text{mA}$	–	–	2.6	V
Small–Signal Characteristics						
Current Gain–Bandwidth Product	f_T	$I_C = 50\text{mA}, V_{CE} = 20\text{V}, f = 100\text{MHz}, \text{Note 3}$	300	–	–	MHz
Output Capacitance	C_{obo}	$V_{CB} = 10\text{V}, I_E = 0, f = 1\text{MHz}$	–	–	8	pF
Input Capacitance	C_{ibo}	$V_{EB} = 2\text{V}, I_C = 0, f = 1\text{MHz}$	–	–	30	pF
Switching Characteristics						
Turn–On Time	t_{on}	$V_{CC} = 30\text{V}, I_C = 150\text{mA}, I_{B1} = 15\text{mA}$	–	–	45	ns
Delay Time	t_d		–	–	10	ns
Rise Time	t_r		–	–	40	ns
Turn–On Time	t_{off}	$V_{CC} = 6\text{V}, I_C = 150\text{mA}, I_{B1} = I_{B2} = 15\text{mA}$	–	–	100	ns
Delay Time	t_s		–	–	80	ns
Rise Time	t_f		–	–	30	ns

Note 3. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [NTE manufacturer](#):

Other Similar products are found below :

[619691C](#) [MCH4017-TL-H](#) [MJ15024/WS](#) [MJ15025/WS](#) [BC546/116](#) [BC556/FSC](#) [BC557/116](#) [BSW67A](#) [HN7G01FU-A\(T5L,F,T](#)
[NJVMJD148T4G](#) [NSVMMBT6520LT1G](#) [NTE187A](#) [NTE195A](#) [NTE2302](#) [NTE2330](#) [NTE2353](#) [NTE316](#) [IMX9T110](#) [NTE63](#) [NTE65](#)
[C4460](#) [SBC846BLT3G](#) [2SA1419T-TD-H](#) [2SA1721-O\(TE85L,F\)](#) [2SA1727TLP](#) [2SA2126-E](#) [2SB1202T-TL-E](#) [2SB1204S-TL-E](#) [2SC5488A-](#)
[TL-H](#) [2SD2150T100R](#) [SP000011176](#) [FMC5AT148](#) [2N2369ADCSM](#) [2SB1202S-TL-E](#) [2SC2412KT146S](#) [2SC4618TLN](#) [2SC5490A-TL-H](#)
[2SD1816S-TL-E](#) [2SD1816T-TL-E](#) [CMXT2207 TR](#) [CPH6501-TL-E](#) [MCH4021-TL-E](#) [BC557B](#) [TTC012\(Q\)](#) [BULD128DT4](#) [JANTX2N3810](#)
[Jantx2N5416](#) [US6T6TR](#) [KSF350](#) [068071B](#)