



ELECTRONICS, INC.  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089  
<http://www.nteinc.com>

**NTE7189, NTE7190, NTE7191, NTE7192,  
 NTE7193, NTE7194 & NTE7195  
 Integrated Circuit  
 Pulse Width Modulator (PWM) Switch for  
 TVs, Monitors and Audio Amplifiers**

**Description:**

The NTE7189 thru NTE7195 are off-line pulse width modulator switches in a TO220 type package bringing many new enhancements that reduce the sensitivity to board layout and line transients making design even easier. These devices incorporate all the functions necessary for a switched mode control system into a three terminal monolithic IC: power MOSFET, PWM controller, high voltage start up circuit, loop compensation and fault protection circuitry.

**Features:**

- Cost Competitive with Linears Above 5W
- Very Low AC/DC Losses – Up to 90% Efficiency
- Built-In Auto-Restart and Current Limiting
- Latching Thermal Shutdown for System Level Protection
- Implements Flyback, Forward, Boost or Buck Topology
- Works with Primary or Opto Feedback
- Stable in Discontinuous or Continuous Conduction Mode
- Source Connected Tab for Low EMI

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$ , All Voltages Referenced to Source unless otherwise specified)

Drain Voltage .....	-0.3V to +700V
Drain Current Increase ( $\Delta I_p$ ) in 100ns except during blanking time (Note 1) .....	$0.1 \times I_{LIMIT(MAX)}$
Control Voltage .....	-0.3V to +9V
Control Current .....	100mA

Note 1. Related to transformer saturation.

**Absolute Maximum Ratings (Cont'd):** ( $T_A = +25^\circ\text{C}$ , All Voltages Referenced to Source unless otherwise specified)

Power Output Level,  $P_{MAX}$

Single Voltage Input (100/115/230 VAC,  $\pm 15\%$ , Note 2, Note 3, Note 4)

NTE7189	12W
NTE7190	25W
NTE7191	50W
NTE7192	75W
NTE7193	100W
NTE7194	125W
NTE7195	150W

Wide Range Input (85 to 265 VAC, Note 3, Note 4)

NTE7189	7W
NTE7190	15W
NTE7191	30W
NTE7192	45W
NTE7193	60W
NTE7194	75W
NTE7195	90W

Operating Junction Temperature (Note 5),  $T_j$  .....  $-40^\circ$  to  $+150^\circ\text{C}$

Storage Temperature Range,  $T_{stg}$  .....  $-65^\circ$  to  $+150^\circ\text{C}$

Lead Temperature (During Soldering, 1/16" from case, 5sec max.),  $T_L$  .....  $+260^\circ\text{C}$

Maximum Thermal Resistance, Junction-to-Ambient (Note 6),  $R_{thJA}$  .....  $+70^\circ\text{C/W}$

Maximum Thermal Resistance, Junction-to-Case (Note 7),  $R_{thJC}$  .....  $+2^\circ\text{C/W}$

Note 2. 110/115 VAC with doubler input.

Note 3. Assumes appropriate heat sinking to keep the maximum junction temperature below  $100^\circ\text{C}$

Note 4.  $P_{MAX}$  is the maximum practical continuous power output level for conditions shown. The continuous power capability in a given application depends on thermal environment, transformer design, efficiency required, minimum specified input voltage, input storage capacitance, etc.

Note 5. Normally limited by internal circuitry.

Note 6. Free standing with no heatsink.

Note 7. Measured at tab closest to plastic interface or Source pin.

**Electrical Characteristics:** (Source = 0V,  $T_J = -40^\circ$  to  $+125^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
<b>Control Functions</b>							
Output Frequency	$f_{OSC}$	$I_C = 4\text{mA}$ , $T_J = +25^\circ\text{C}$	90	100	110	kHz	
Maximum Duty Cycle	$D_{MAX}$	$I_C = I_{CD1} + 0.4\text{mA}$	64	67	70	%	
Minimum Duty Cycle	$D_{MIN}$	$I_C = 10\text{mA}$	0.7	1.7	2.7	%	
PWM Gain		$I_C = 4\text{mA}$ , $T_J = +25^\circ\text{C}$	-21	-16	-11	%/mA	
PWM Gain Temperature Drift			-	-0.05	-	%/mA/ $^\circ\text{C}$	
External Bias Current	$I_B$		0.8	2.0	3.3	mA	
Dynamic Impedance	$Z_C$	$I_C = 4\text{mA}$ , $T_J = +25^\circ\text{C}$	10	15	22	W	
Dynamic Impedance Temperature Drift			-	0.18	-	%/ $^\circ\text{C}$	
<b>Shutdown/Auto-Restart</b>							
Control Pin Charging Current	$I_C$	$T_J = +25^\circ\text{C}$	$V_C = 0\text{V}$	-2.4	-1.9	-1.2	mA
			$V_C = 5\text{V}$	-2	-1.5	-0.8	
Charging Current Temperature Drift		Note 8	-	0.4	-	%/ $^\circ\text{C}$	

Note 8. For specifications with negative values, a negative temperature coefficient corresponds to an increase in magnitude with increasing temperature, and a positive temperature coefficient corresponds to a decrease in magnitude with increasing temperature.

**Electrical Characteristics (Cont'd):** (Source = 0V,  $T_J = -40^\circ$  to  $+125^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
<b>Shutdown/Auto-Restart (Cont'd)</b>							
Auto-Restart Threshold Voltage	$V_{C(AR)}$	S1 open	-	5.7	-	V	
UV Lockout Threshold Voltage		S1 open	4.4	4.7	5.0	V	
Auto-Restart Hysteresis Voltage		S1 open	0.6	1.0	-	V	
Auto-Restart Duty Cycle NTE7189, NTE7190		S1 open	2	5	9	%	
All Other Devices			2	5	8		
Auto-Restart Frequency		S1 open	-	1.2	-	Hz	
<b>Circuit Protection</b>							
Self-Protection Current Limit NTE7189	$I_{LIMIT}$	$di/dt = 40\text{mA}/\mu\text{s}$	$T_J = +25^\circ\text{C}$	0.23	0.25	0.28	A
NTE7190		$di/dt = 80\text{mA}/\mu\text{s}$		0.45	0.50	0.55	A
NTE7191		$di/dt = 160\text{mA}/\mu\text{s}$		0.90	1.00	1.10	A
NTE7192		$di/dt = 240\text{mA}/\mu\text{s}$		1.35	1.50	1.65	A
NTE7193		$di/dt = 320\text{mA}/\mu\text{s}$		1.80	2.00	2.20	A
NTE7194		$di/dt = 400\text{mA}/\mu\text{s}$		2.25	2.50	2.75	A
NTE7195		$di/dt = 480\text{mA}/\mu\text{s}$		2.70	3.00	3.30	A
Initial Current Limit		$I_{INIT}$		$\leq 85\text{VAC}$ (Rectified Line Input)	$T_J = +25^\circ\text{C}$	$0.75 \times I_{LIMIT(MIN)}$	-
	$\leq 265\text{VAC}$ (Rectified Line Input)		$0.6 \times I_{LIMIT(MIN)}$	-		-	A
Leading Edge Blanking Time	$t_{LEB}$	$I_C = 4\text{mA}$ , $T_J = +25^\circ\text{C}$	-	180	-	ns	
Current Limit Delay	$t_{ILD}$	$I_C = 4\text{mA}$	-	100	-	ns	
Thermal Shutdown Temperature		$I_C = 4\text{mA}$	125	135	-	$^\circ\text{C}$	
Power-Up Reset Threshold Voltage	$V_{C(RESET)}$	S2 open	2.0	3.3	4.3	V	
<b>Output</b>							
On-State Resistance NTE7189	$R_{DS(ON)}$	$I_D = 25\text{mA}$	$T_J = +25^\circ\text{C}$	-	31.2	36.0	W
			$T_J = +100^\circ\text{C}$	-	51.4	60.0	W
NTE7190		$I_D = 50\text{mA}$	$T_J = +25^\circ\text{C}$	-	15.6	18.0	W
			$T_J = +100^\circ\text{C}$	-	25.7	30.0	W
NTE7191		$I_D = 100\text{mA}$	$T_J = +25^\circ\text{C}$	-	7.8	9.0	W
			$T_J = +100^\circ\text{C}$	-	12.9	15.0	W
NTE7192		$I_D = 150\text{mA}$	$T_J = +25^\circ\text{C}$	-	5.2	6.0	W
			$T_J = +100^\circ\text{C}$	-	8.6	10.0	$\Omega$
NTE7193		$I_D = 200\text{mA}$	$T_J = +25^\circ\text{C}$	-	3.9	4.5	W
			$T_J = +100^\circ\text{C}$	-	6.4	7.5	W
NTE7194		$I_D = 250\text{mA}$	$T_J = +25^\circ\text{C}$	-	3.1	3.6	W
			$T_J = +100^\circ\text{C}$	-	5.2	6.0	W
NTE7195		$I_D = 300\text{mA}$	$T_J = +25^\circ\text{C}$	-	2.6	3.0	W
			$T_J = +100^\circ\text{C}$	-	4.3	5.0	W


**Electrical Characteristics (Cont'd):** (Source = 0V,  $T_J = -40^\circ$  to  $+125^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>Output (Cont'd)</b>						
OFF-State Current	$I_{DSS}$	$V_{DS} = 560\text{V}$ , $T_A = +125^\circ\text{C}$ , Note 9	-	-	250	$\mu\text{A}$
Breakdown Voltage	$BV_{DSS}$	$I_D = 100\mu\text{A}$ , $T_A = +25^\circ\text{C}$ , Note 9	700	-	-	V
Rise Time	$t_R$	Measured in a Typical Flyback Converter Application.	-	100	-	ns
Fall Time	$t_F$		-	50	-	ns
Drain Supply Voltage		Note 10	36	-	-	V
Shunt Regulator Voltage	$V_{C(SHUNT)}$	$I_C = 4\text{mA}$	5.5	5.7	6.0	V
Shunt Regulator Temperature Drift			-	$\pm 50$	-	ppm/ $^\circ\text{C}$
Control Supply/Discharge Current NTE7189 thru NTE7192	$I_{CD1}$	Output MOSFET Enabled	0.6	1.2	1.6	mA
NTE7193, NTE7194, NTE7195			0.7	1.4	1.8	mA
All Devices	$I_{CD2}$	Output MOSFET Disabled	0.5	0.8	1.1	mA

Note 9. The breakdown voltage and leakage current measurements can be accomplished by using the following sequence:

- i. The curve tracer should initially be set at 0V. The base output should be adjusted through a voltage sequence of 0V, 6.5V, 4.3V, and 6.5V. The base current from the curve tracer should not exceed 100mA. This CONTROL pin sequence interrupts the Auto-Restart sequence and locks the internal MOSFET in the OFF state.
- ii. The breakdown and leakage measurements can now be taken with the curve tracer. The maximum voltage from the curve tracer must be limited to 700V under all conditions.

Note 10. It is possible to start up and operate at DRAIN voltages well below 36V. However, the CONTROL pin charging current is reduced, which affects start-up time, auto-restart frequency, and auto-restart duty cycle.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Audio Amplifiers](#) category:*

*Click to view products by [NTE manufacturer](#):*

Other Similar products are found below :

[LV47002P-E](#) [NCP2890AFCT2G](#) [NTE1192](#) [LC706200CM](#) [IS31AP4915A-QFLS2-TR](#) [TDA1591T](#) [TS2012EIJT](#) [NCP2809BMUTXG](#)  
[NJW1157BFC2](#) [IS31AP4996-GRLS2-TR](#) [NCP2823BFCT1G](#) [BD88420GUL-E2](#) [LA4450L-E](#) [IS31AP2036A-CLS2-TR](#) [NTE1110](#) [NTE7100](#)  
[NTE7114](#) [NTE7163](#) [NTE7168](#) [NTE7177](#) [NTE7178](#) [NTE7186](#) [NTE7198](#) [NTE7202](#) [NTE7217](#) [BD88400GUL-E2](#) [BD88200GUL-E2](#)  
[SABRE9601K](#) [THAT1646W16-U](#) [PAM8965ZLA40-13](#) [TSDP10XX1NLGXZBX](#) [TSDP11XX1NKGIZBX](#) [TSDP11XX1NLGXZBX](#)  
[TSDP10XX1NKGIZBX](#) [NJM4580CV-TE1](#) [NJU7084R-TE1](#) [OPA1655DR](#) [LV4910T-MPB-E](#) [NCP2890AFCT2](#) [NCV2211DR2G](#)  
[SCY99091FCT2G](#) [TAS5720MRSMR](#) [AW87389FCR](#) [AW8737AFCR](#) [TDA2005R](#) [TDA2030](#) [TDA7265L-J11-A-T](#) [CD2050CZ](#)  
[AW88261FCR](#) [TDA7377-JSM](#)