



ELECTRONICS, INC.  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089  
<http://www.nteinc.com>



## NTE7228 Integrated Circuit Fixed Multi-Output Positive Voltage Regulator 10-Lead SIP

**Description:**

The NTE7228 is a multi-output positive voltage regulator in a 10-Lead SIP type package designed to provide fixed precision output voltages of 5.1V & 8V at current up to 0.5A and 12V at current up to 1A with an external PNP transistor. An internal reset circuit generates a reset pulse when Output 1 decreases below the regulated value. Output 2 and Output 3 can be disabled by TTL input. Protection features include over voltage protection, short circuit protection and thermal shutdown.

**Features:**

- Output Currents up to 0.5A (Output 1 & Output 2)
- Output Current up to 1A with External Transistor (Output 3)
- Fixed Precision Output 1 Voltage 5.1V  $\pm 2\%$
- Fixed Precision Output 2 Voltage 8V  $\pm 2\%$
- Control Signal Generator for Output 3 Voltage (12V  $\pm 2\%$ )
- Reset Facility for Output Voltage 1
- Output 2 and Output 3 with Disable by TTL Input
- Current Limit Protection at Each Output
- Thermal Shutdown

**Absolute Maximum Ratings:**

DC Input Voltage, $V_{IN}$ .....	20V
Disable Input Voltage, $V_C$ .....	20V
Output Current, $I_O$ .....	0.5A
Power Dissipation (No Heatsink), $P_D$ .....	1.5W
Junction Temperature, $T_J$ .....	+150°C
Operating Temperature Range, $T_{opr}$ .....	0° to +125°C



**Electrical Characteristics:** ( $V_{IN1} = 7.5V$ ,  $V_{IN2} = 10.5V$ ,  $T_J = +25^\circ C$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Output Voltage 1	$V_{O1}$	$7.5V < V_{IN1} < 14V$	$I_{O1} = 10mA$	5.0	5.1	5.2	V
			$5mA < I_{O1} < 500mA$	4.9	5.1	5.3	V
Output Voltage 2	$V_{O2}$	$10.5V < V_{IN2} < 18V$	$I_{O2} = 10mA$	7.84	8.0	8.16	V
			$5mA < I_{O2} < 500mA$	7.7	8.0	8.3	V
Dropout Output Voltage	$V_{D1}$	$I_{O1} = 500mA$	–	–	2.5	V	
	$V_{D2}$	$I_{O2} = 500mA$	–	–	2.5	V	
Line Regulation	$\pm V_{O1}$	$I_{O1} = I_{O2} = 200mA$	$7.5V < V_{IN1} < 14V$	–	–	50	mV
	$\pm V_{O2}$		$10.5V < V_{IN2} < 18V$	–	–	80	mV
Load Regulation	$\pm V_{O1}$	$5mA < I_{O1} < 500mA$	–	–	100	mV	
	$\pm V_{O2}$	$5mA < I_{O1} < 500mA$	–	–	160	mV	
Output Voltage 3	$V_{O3}$	$V_{SYS} = 13V$ , $I_{O3} = 100mA$	11.7	12.0	12.3	V	
Line Regulation 3	$\pm V_{O3}$	$13V < V_{IN2} < 18V$ , $I_{O3} = 100mA$	–	–	120	mV	
Load Regulation 3	$\pm V_{O3}$	$5mA < I_{O3} < 1A$	–	–	250	mV	
Reset Pulse Delay	$T_{rd}$	$C_D = 100nF$ , Note 1	–	25	–	ms	
Saturation Voltage in Reset Condition	$V_{rL}$	$I_6 = 5mA$	–	–	0.4	V	
Leakage Current at Pin6	$I_{rH}$	$V_6 = 10V$	–	–	10	$^\circ A$	
Output Voltage Thermal Drift	$ST_t$	$0^\circ < T_J < +125^\circ C$ , Note 2	–	100	–	ppm/ $^\circ C$	
Short Circuit Output Current	$I_{SC1}$	$V_{IN1} = 7.5V$	–	–	1.6	A	
	$I_{SC2}$	$V_{IN2} = 10.5V$	–	–	1.6	A	
Disable Voltage, High	$V_{disH}$	Output 2 Active	2	–	–	V	
Disable Voltage, Low	$V_{disL}$	Output 2 Disabled	–	–	0.8	V	
Disable Bias Current	$I_{dis}$	$0V < V_{dis} < 7V$	–100	–	2	$^\circ A$	
Junction Temperature for TSD	$T_{tsd}$	Note 2	–	145	–	$^\circ C$	
Quiescent Current	$I_q$	$I_{O1} = 10mA$ , Output 2 Disabled	–	–	2	mA	
Reset Threshold Voltage	$V_r$	$K = V_{O1}$	K-0.4	K-0.25	K-0.1	V	
Reset Threshold Hysteresis	$V_{rth}$	Note 1	20	50	100	mA	

Note 1. To check the reset circuit, the reset output is low to discharge the delay capacitor ( $= C_D$ ). If it's less than  $V_{O1} - 0.25V$ . And the reset output is high when the delay capacitor voltage linearly increased by the internal current source ( $10^\circ A$ ) if it's more than  $V_{O1} - 0.2V$ . The equations of delay time is the same as below.  $T_{rd} = (C_D \times 2.5) / 10^\circ A$ .

Note 2. These parameters, although guaranteed, are not 100% tested in production.

**Pin Connection Diagram**  
(Front View)



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Linear Voltage Regulators](#) category:*

*Click to view products by [NTE](#) manufacturer:*

Other Similar products are found below :

[LV56831P-E](#) [LV5684PVD-XH](#) [MCDTSA6-2R](#) [L7815ACV-DG](#) [PQ3DZ53U](#) [LV56801P-E](#) [L78LR05DL-MA-E](#) [636416C](#) [714954EB](#)  
[ZMR500QFTA](#) [BA033LBSG2-TR](#) [LV5680P-E](#) [L78M15CV-DG](#) [L79M05T-E](#) [L78LR05D-MA-E](#) [NCV317MBTG](#) [NTE7227](#) [MP2018GZD-33-P](#) [MP2018GZD-5-P](#) [LV5680NPVC-XH](#) [LT1054CN8](#) [MP2018GZD-5-Z](#) [MP2018GZD-33-Z](#) [ZTS6538SE](#) [MC78L06BP-AP](#)  
[TA78L12F\(TE12L,F\)](#) [TC47BR5003ECT](#) [TCR2LN12,LF\(S](#) [TCR2LN28,LF\(S](#) [TCR2LN30,LF\(S](#) [TCR3DF295,LM\(CT](#) [TCR3DF40,LM\(CT](#)  
[MC7812BD2TG](#) [TPS549B22RVFT](#) [BA178M20CP-E2](#) [L78M05TL-TL-E](#) [L78M05T-TR-E](#) [L78M12ABDT](#) [LM7812SX/NOPB](#) [LR645N3-G-P003](#) [LR645N3-G-P013](#) [ZXTR2005P5-13](#) [SCD7812BTG](#) [TCR3DF335,LM\(CT](#) [ZXTR2012K-13](#) [TLE42994E V33](#) [ZXTR2012Z-13](#)  
[ZXTR2012P5-13](#) [ZXTR2008K-13](#) [ZXTR2005K-13](#)