

Technical data sheet

Spacer DSK 45

Item no. 6416500



Spacer for use in U 5 support and in the head plate, type KU 7 VQP.



St	Steel
FT	Hot-dip galvanised

Additional product text, instruction	For static reasons, the spacer is always used to increase stability to prevent the support from deforming when the bracket is tightened with the hexagonal bolts.
--------------------------------------	---

Master data

Item no.	6416500
Type	DSK 45 FT
Description 1	Spacer
Description 2	for use in US 5 support
Dimension	80x45x40
Material	Steel
Material symbol	St
Surface	Hot-dip galvanised
Surface to DIN	DIN EN ISO 1461
Surface symbol	FT
Smallest sales unit (VG)	20,00 Piece
Weight	18,00 kg/100 pc.


Technical data sheet

Spacer DSK 45

Item no. 6416500



Technical data



Length	80,00 mm
Width	45,00 mm
Side height	40,00 mm
Dimension	80 x 45 x 40 x 2,5 mm
Version	Other
Suitable for	U profile
With screw accessories	<input type="checkbox"/>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Ducting & Raceways](#) category:

Click to view products by [OBO BETTERMANN](#) manufacturer:

Other Similar products are found below :

[802A-ECSP](#) [923223-000](#) [A0405538](#) [1301170070](#) [1301230153](#) [1302263178](#) [1302263259](#) [1302264375](#) [1301170051](#) [1301180002](#)
[1301230130](#) [1302264137](#) [1302264218](#) [AX102261](#) [AX102652](#) [AX102653](#) [AX102654](#) [AX102657](#) [AX102737](#) [NP24BK](#) [NP265W](#) [NP8LA](#)
[A0405537](#) [TAPC2-2/0-X](#) [43-215](#) [AX100383](#) [TTSL2VC3-5-Y](#) [556029-4](#) [UTPSP3GYY](#) [DD2J](#) [WMPFS](#) [NP720I](#) [WB22543A01](#) [569088-3](#)
[1302264205](#) [1301170059](#) [1302264388](#) [1302263854](#) [1302263180](#) [1301230154](#) [803A-TSP](#) [1301180028](#) [801A-JCSP](#) [801A-LSP](#) [801A-TSP](#)
[802A-LSP](#) [802A-TSP](#) [803A-ECSP](#) [803A-ICSP](#) [3066](#)