

Technical data sheet

Aluminium empty housing Mx06-Mx15, paintable

Art.-Nr. 2011392



Robust aluminium empty housing for mechanical engineering and automation technology. The OBO Mx series' excellent features make it most suitable for extreme demands in all different areas. It is therefore also best suited for applications in industry, ports and shipbuilding, as well as in the agricultural sector.

The series' properties protect the electrical installation when under extreme strain. The products withstand both great cold and heat as well as impacts or kicks on roads, railways or in tunnels. With a protection class of up to IP66, they are optimally protected against the intrusion of water. The aluminium is of course UV-resistant and halogen-free. The cover seal is made from polyurethane.

The aluminium housings are sandblasted and are delivered with a cover including stainless steel screws, a seal and 2 or 4 earthing screws.

The surface provides a good contact when using metal fittings.



AIG Die-cast aluminium
Cr3 Chrome III coating

Additional product text 1 | Temperature: -40°C to +125°C

Master data

| | |
|---------------------|-------------------------|
| Item no. | 2011392 |
| Type | Mx 161609 CR3 |
| Description 1 | Aluminium empty housing |
| Description 2 | surface can be coated |
| Dimension | 160x160x90 |
| Material | Die-cast aluminium |
| Material symbol | AIG |
| Surface | Chrome III coating |
| Surface symbol | Cr3 |
| Smallest sales unit | 1,00 Piece |
| Weight | 170,00 kg/100 pc. |



Technical data sheet

Aluminium empty housing Mx06-Mx15, paintable

Art.-Nr. 2011392



Technical data



| | |
|--|--|
| Length | 150,00 mm |
| Width | 100,00 mm |
| Height | 91,00 mm |
| Clear internal dimensions | 140,5x90x74,5 mm |
| Dimension | 150X100X80 mm |
| Dimension LxWxH | 150x100x91 mm |
| Extension option | <input checked="" type="checkbox"/> |
| Version | Closed with 4 stainless steel lid screws |
| Lid version | Closed |
| Cover fastening | Screwed |
| Shape | Rectangular |
| Suitable for outdoor use | <input checked="" type="checkbox"/> |
| Suitable for lightning protection with lid | <input type="checkbox"/> |
| Yes | Yes |
| With cover | <input checked="" type="checkbox"/> |
| With mounting plate | <input type="checkbox"/> |
| Installation type | Wall/ceiling mounting |
| Protection rating | IP66 |
| Protection rating | IP 66 |
| max. permitted ambient temperature | -40,00 - 125,00 °C |
| Weatherproof | <input checked="" type="checkbox"/> |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Enclosures, Boxes & Cases](#) category:

Click to view products by [OBO BETTERMANN](#) manufacturer:

Other Similar products are found below :

[585-R-WH-PK](#) [M-10-PLATED](#) [60221-01](#) [60566-01-000](#) [HPL-9VB BATT DOOR](#) [M18-PLTD](#) [M-21-PLATED](#) [63310-01-000](#) [6711GSKT](#)
[71884-29-028](#) [LH45-100 Black](#) [72868-510-000](#) [CNS-0000 Black](#) [72883-510-000](#) [CNS-0101 Black](#) [72906-510-000](#) [CNS-0407 Black](#) [73092-](#)
[510-000](#) [CNM-0101 Black](#) [73105-510-000](#) [CNL-0101 Black](#) [73108-510-000](#) [CNL-0303 Black](#) [73395-510-039](#) [CNS-0006 Bone](#) [74016-510-000](#)
[CNL-0006 Black](#) [74257-510-000](#) [CNL-0004](#) [MDC-1183-PLAIN-ALUM](#) [MDC-1183-PTD](#) [MDC-13104-PTD](#) [MDC-321-PTD](#) [MDC-973-PTD](#)
[76](#) [77153-01-028](#) [FLX6030](#) [83535-01-508](#) [90026-501-000](#) [PS36-200](#) [116-508](#) [120-407](#) [120-910](#) [127-908](#) [130-008](#) [1301170079](#)
[1322GSKTEP](#) [1325GSKT3](#) [138-PLAIN](#) [1434-1210](#) [EAS-500 \(BLACK ANO\)](#) [1804RP-RB-PK](#) [190-005](#) [2202307](#) [KAB3321 BLACK](#)
[KAB3421](#) [2697466](#) [S52213](#) [2901123](#) [2901699](#) [A0645271](#) [A20P20](#)