

# Technical data sheet

## Distribution box, 9 division units, with screwless terminal

Art.-Nr. 2008848



The OBO small distributor series offers secure current distribution, both indoors and outdoors. The surface-mounted small distributors fulfil all the requirements of IEC 439-3 and are available in different sizes with three to twelve division units.

There are three equipment variants: With screw terminals, with screwless terminals and without terminals. All the sizes and equipment variants are available in two materials. All the small distributors are supplied with a pre-mounted 35 hat profile support rail.

The small distributors with terminal strips also contain an accessories set, which also comprises a sheet of stickers. The self-adhesive pictograms make the often annoying labelling of the individual division units superfluous. Should labelling be required, then the appropriate stickers are available on the sticker sheet.

The high protection rating (IP66) and the robust construction (IK07 at -25 °C) ensure safe operation, even under difficult environmental circumstances. With unprotected outdoor use, we recommend protecting the small distributors against direct weather influences from above.

The increased spacing between the hat profile support rail and the rear panel of the small distributor makes wiring work considerably easier: Cables are run quickly and simply behind the devices. The cables can be inserted into the interior of the small distributor from above, from below and from the rear, making wiring significantly easier and improving the appearance of the housing.



PC Polycarbonate

Additional product text, instruction	Surface-mounted distribution box, with protective insulation for max. 9 division units. There are 9 break-out openings (8x Ø20 and 1x Ø20/25/32) on both the upper and lower sides incl. pre-mounted 35 mm hat profile support rail. The four screw cover caps supplied prevent unwanted "voltage carry over".
Additional product text 1	Suitable for interior and exterior mounting; VDE-tested to DIN EN 61439; Accessories: · Terminal strip set consisting of: One PE/N terminal (1x25 mm <sup>2</sup> and 1x16 mm <sup>2</sup> screw terminal points, 2x4 mm <sup>2</sup> and 12x2.5 mm <sup>2</sup> screwless terminals), mini hat profile rail, mounting instructions and fastening set · Self-adhesive pictograms for installation labelling · Six elastic cable entries Ø20 mm for cable diameters 0–17 mm · One elastic cable entry Ø25 mm for cable diameter 0–22 mm · One elastic cable entry Ø32 mm for cable diameter 0–28 mm · Two stainless steel external fastenings · Cover strip for closing off unused separation units
Additional product text 2	Nominal current 63 A Power loss at 40 K 20.7 W

### Master data

Item no.	2008848
Type	SDB 09 PC
Description 1	Small distributor
Description 2	for max. 9 distribution units
Dimension	240x191x125
Colour	Light grey
RAL number	7035
Material	Polycarbonate
Material symbol	PC
Smallest sales unit	1,00 Piece
Weight	103,84 kg/100 pc.

# Technical data sheet

Distribution box, 9 division units, with screwless terminal

Art.-Nr. 2008848



## Technical data

Length	240,00 mm
Width	191,00 mm
Height	125,00 mm
Dimension LxWxH	240x191x125 mm
Extension option	<input checked="" type="checkbox"/>
Number of rows	1,00
Cover type	Cover
Lid version	With cut-out
Width in divisional units	9,00
DIN rail	<input checked="" type="checkbox"/>
Installation location	Protected outdoor area
EMC version	<input type="checkbox"/>
Glow wire test	650,00 °C
Terminals	Connector
With cover	<input type="checkbox"/>
With mounting plate	<input type="checkbox"/>
With lock	<input type="checkbox"/>
Mounting type	Structure
Nominal voltage	400,00 V
Nominal operating voltage	400,00 V
Nominal current	63,00 A
Nominal insulating voltage AC	1.000,00 V
Nominal insulating voltage DC	1.500,00 V
Protection rating	IP66
Protection rating IK code	IK06
Transparent lid	<input checked="" type="checkbox"/>
Permitted power loss	Kleinverteiler Leistung Temperaturerhöhung SDB 09 4,0 W 10 K SDB 09 10,0 W 20 K SDB 09 16,0 W 30 K SDB 09 20,0 W 40 K SDB 09 33,0 W 80 °C

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Electrical Enclosures](#) category:*

*Click to view products by [OBO BETTERMANN](#) manufacturer:*

Other Similar products are found below :

[1201110001](#) [120-401](#) [120-905](#) [120-909](#) [120-403](#) [130-004](#) [MR-25L+](#) [30-8739](#) [PIP-11774SCREW](#) [30-9715](#) [30-9777-BU](#) [110-902](#) [110-901](#)  
[A16N12BLP](#) [110-406](#) [110-401](#) [110-404](#) [120-405](#) [34861601](#) [106-009](#) [106-505](#) [105-405](#) [111-005](#) [127-909](#) [106-502](#) [130-475](#) [130-503](#) [127-](#)  
[455](#) [9511150](#) [9511017](#) [9820011](#) [NSYTDB5PL](#) [137-455](#) [130-001](#) [105-904](#) [120-404](#) [137-005](#) [130-505](#) [127-406](#) [AB 1,5.0](#) [AB2.0](#) [ABM.0](#)  
[73345601](#) [F-MP](#) [H-MP](#) [M-MP](#) [PAT 12040](#) [2461000](#) [9121230](#) [79541301](#)