

Straight plug with screw-lock cable assembly, USB 5 Gbit/s

General information

Part number	CC10WAM124IYS
Part no. without assembly	C10WAM-P12XMM0-0000
Termination	Solder
Size	0
Locking principle	Break-Away , Screwlocking
Coding	A (light brown)
Cable Diameter	5.7 mm
Cable outlet	Overmolding
Second side	ODU connector
Bend relief color	Black



Illustrations may differ from original product.
Dimensions, unless otherwise specified, in mm.

CODING:A

POSITIONS: 12 positions

DIMENSIONS:

The pin layout corresponds to the view on the termination area

Contact insert description

Number of contacts	12
Contact type	Pins
Contact diameter	10x 0.3 mm. 2x 0.7 mm
Insulator material	PEEK
Termination	Solder
Data transmission	USB 3.2 Gen 1x1 (5 Gbit/s)

Reverse gender on request

Cable description

Cable type	USB cable 3.2 Gen1x1 - By the meter
UL style	style20693
Conductor	Tin plated copper
Cable color	Black
Wire cross section	AWG 28

Technical information

Nominal current single contact	1 A; 5 A	IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003)
Test voltage	0.5 kV AC	EIA-364-20F:2019-02

All shown connectors are rated to a safety extra low voltage (SELV) of less than 50 V AC / 75 V DC, according to IEC 61140:2016 (VDE 0140-1:2016) Protection against electric shock - Common aspects for installation and equipment. In case other standards rule a specific use of the connector, the application specific safety criteria shall be considered first. In this context, lower voltage ratings may be valid. Warning: Danger to life for operating voltages above 50 V AC / 120 V DC!

Mechanical and environmental data

Degree of protection*	IP6K8 / IP6K9K
Operating temperature	-40 °C – 80 °C
Mating cycles	5000

*mated condition

Material and surface treatments


Housing	Cu-alloy with ruthenium finish
Contact	Cu-alloy with gold finish

All shown connectors are defined without breaking capacity (COC) according to IEC 61984:2008 (VDE 0627:2009). The contact arrangement of an ODU data transmission connector differs from a standard data transmission connector due to the robust ODU specific design. However, the ODU design meets the electrical specifications of the respective standard data transmission protocol.

ODU MEDI-SNAP® and MINI-SNAP® are UL-approved (E110586).

ODU reserves the right to make changes based on the current state of knowledge without prior notice without being obliged to provide replacement deliveries or refinements of older designs.

Cable length tip-to-tip



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Cables / IEEE 1394 Cables category](#):

Click to view products by [ODU manufacturer](#):

Other Similar products are found below :

[88764-0800](#) [148700-1](#) [AC102012-1](#) [AC102012-2](#) [FTP-629Y601](#) [45-1345-15](#) [45-1358-15](#) [45-1363-15](#) [IP-USB1\(C10\)S-RW](#)
[CABLE/RTP/USB/DT](#) [45-1351-15](#) [45-1357-15](#) [45-1433-1](#) [10115240-12200LF](#) [RS232-AB2](#) [687680278](#) [MDM9PH004B](#) [FTP-629Y401](#)
[FTP-628Y402](#) [UPMAB-1M](#) [CA-USB-AM/CM-1FT](#) [CA-USB-AM/AF-6FT](#) [CA-USB3-AM/BM-3FT](#) [CA-USB3-AM/AF-3FT](#) [CA-USB3-](#)
[AM/AF-10FT](#) [UA-30AMFM-SL7B01](#) [UA-30AMFM-SL7B03](#) [UES-1001A160](#) [UES-1003A160](#) [USBFTV2PEMSA2N10OPEN](#)
[USBCAMCM100](#) [USB A/F*2 to 2.54 2*5P-SH L=400mm](#) [103-1020-BL-00100](#) [103-1030-BL-F0300](#) [103-1092-BL-F0200](#) [105-1092-BL-](#)
[00300](#) [105-1092-BL-00200](#) [105-1031-BL-00200](#) [105-1032-RE-B0200](#) [103-1020-BL-00200](#) [9370-P](#) [9372-0-15-01-13-14-10-0](#)
[USBFTV2SA2G10OPEN](#) [103-1030-BL-F0200](#) [105-1032-RE-B0050](#) [105-1032-SV-B0200](#) [10-00003](#) [BERTVW19](#) [KUCA1](#) [3004-235](#)