




Square flange receptacle for rear or front panel mounting with backshell,  
MIL-DTL-38999

General information

|                   |                                       |
|-------------------|---------------------------------------|
| Part number       | GFTAATO-H005SN-0000                   |
| Termination       | Crimp                                 |
| Size              | 12 (STD 38999)                        |
| Locking principle | Break-Away , Push-Pull , Screwlocking |
| Coding            | A (light brown)                       |
| Cable Diameter    | 5 – 14.6 mm                           |
| Cable outlet      | Backshell                             |



The pin layout corresponds to the view on the termination area

Contact insert description

|                    |             |
|--------------------|-------------|
| Number of contacts | 5           |
| Contact type       | Sockets     |
| Contact diameter   | 1.6 mm      |
| Insulator material | PEEK        |
| Wire cross section | AWG 16 – 20 |
| Termination        | Crimp       |

Technical information

|                                |           |                                            |
|--------------------------------|-----------|--------------------------------------------|
| Nominal current single contact | 13 A      | IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003) |
| Test voltage                   | 1.8 kV AC | EIA-364-20F:2019-02                        |

All shown connectors are rated to a safety extra low voltage (SELV) of less than 50 V AC / 75 V DC, according to IEC 61140:2016 (VDE 0140-1:2016) Protection against electric shock - Common aspects for installation and equipment. In case other standards rule a specific use of the connector, the application specific safety criteria shall be considered first. In this context, lower voltage ratings may be valid. Warning: Danger to life for operating voltages above 50 V AC / 120 V DC!

## Mechanical and environmental data

|                       |                 |
|-----------------------|-----------------|
| Degree of protection* | IP6K8 / IP6K9K  |
| Operating temperature | -65 °C – 175 °C |
| Mating cycles         | 500             |

\*mated condition

## Material and surface treatments

|         |                           |
|---------|---------------------------|
| Contact | Cu-alloy with gold finish |
|---------|---------------------------|

All shown connectors are defined without breaking capacity (COC) according to IEC 61984:2008 (VDE 0627:2009).

The contact arrangement of an ODU data transmission connector differs from a standard data transmission connector due to the robust ODU specific design. However, the ODU design meets the electrical specifications of the respective standard data transmission protocol.

ODU MEDI-SNAP® and MINI-SNAP® are UL-approved (E110586).

ODU reserves the right to make changes based on the current state of knowledge without prior notice without being obliged to provide replacement deliveries or refinements of older designs.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Standard Circular Connector](#) category:*

*Click to view products by [ODU](#) manufacturer:*

Other Similar products are found below :

[600273N007](#) [6134-336-13149](#) [6134-337-11149](#) [6134-337-2390](#) [6134-341-17149](#) [67-02E12-60PX](#) [680-SMG](#) [CXS3102A181S](#) [75-190218-10P](#) [75-474014-05S](#) [75-474211-03P](#) [75-474618-04P](#) [75-474618-04S](#) [75-474620-07P](#) [799539-000](#) [805-005-07NF11-19PC](#) [805-005-07NF15-7PA](#) [836783-1](#) [866857-1](#) [867865-1](#) [121583-0217](#) [RD10A16-19-P6CS051/1](#) [RD16A14-12-S6CS051/2](#) [1301240268](#) [1301240275](#) [14482](#) [16283-18](#) [1877910-1](#) [206039-3](#) [206323-1](#) [207682-1](#) [CA01COM-E24-28P-B-03](#) [CA06COME14SA7P](#) [JL04-1012CK\(05\)-R](#) [JL04V-2A28-11PE-R](#) [JL04V-2E10SL-3PE-B-R](#) [JL04V-2E20-15PE-B-R](#) [JL04V-2E20-4PE-B-R](#) [JL04V-2E24-10PE\(G\)-B-R](#) [JL04V-6A24-11SE-EB-R](#) [JN1AS04MK1X](#) [JN1HS10PLKS2](#) [JN2AS04MK2X-R](#) [JN2DS10SL3-R](#) [JN2FW15SL1](#) [JR16PK-10S](#) [2-206934-7](#) [24282](#) [25.320.3853.1](#) [3011-05](#)