Power-Mox

Precision Power Thick Film High Voltage/High Resistance Tubular





APPLICATIONS

- Power Transmitters
- Pollution Control Systems
- Industrial Control Systems
- Current pulse limiters
- Vacuum and space application

Ohmite Series The heavy duty construction of the Power-Mox series make them durable in most high voltage industrial applications. This product is well known for its high voltage ratings, low voltage coefficients, very high ohmic values, and resistor divider options. Terminations can be selected to adapt to most mounting schemes.

FEATURES

- Wide resistance ranges
- Outstanding voltage coefficient
- 0.4" diameter ferrule, 0.25"-20 threaded end cap, or radial bands available
- Metal oxide resistive elements

| Resistance | Power | Voltage | Available |
|----------------|-------|---------|---------------|
| Range (Ohms) | @25°C | Rating | Tolerances* |
| 1K to 800,000M | 25W | 20KV | 0.5, 1, 2, 5% |


MOX-F MOX-G 1.5K to 1.000.000M 40W 30KV 0.5, 1, 2, 5% 50W МОХ-Н 2K to 1,000,000M 45KV 0.5, 1, 2, 5% MOX-J 3K to 1,000,000M 75W 60KV 0.5, 1, 2, 5%

SERIES SPECIFICATIONS


CHARACTERISTICS

| Core | Ceramic | |
|-------------------------|--|--|
| Coating | Varnish | |
| Resistance Range | 1K to 1,000,000M | |
| Power Rating | to 75W | |
| Voltage Rating | to 60KV | |
| Operating Temperature | -65°C to +180°C | |
| Temperature Coefficient | 25ppm: 0° to 85°C; 50ppm: -55° to 180°C | |

DIMENSIONS



ORDERING INFORMATION





^{*}Some tolerances are not available over the entire resistance range

Power-Mox Dividers


Precision Power Thick Film High Voltage/High Resistance Tubular Dividers

SERIES SPECIFICATIONS

(dimensions as for Power-Mox)


| Ohmite Series | Resistance Range (Ohms) | Power @25°C | Voltage Rating | Maximum Ratio | Ratio Tolerances |
|------------------|----------------------------|----------------|-------------------|------------------|---------------------|
| MOX-FRD | 20K to 2,500M | 15W | 15KV | 5,000:1 | 1, 2, 5% |
| MOX-GRD | 20K to 4,000M | 30W | 25KV | 5,000:1 | 1, 2, 5% |
| MOX-HRD | 20K to 6,000M | 40W | 35KV | 5,000:1 | 1, 2, 5% |
| MOX-JRD | 20K to 6,000M | 60W | 50KV | 5,000:1 | 1, 2, 5% |

DERATING




POWER-MOX ALTERNATE TERMINALS


"01" Lead
"Power-Mox RD" Series
with silver terminations




"02" Lead
"Power-Mox" Series with
radial band option



"03" Lead
"Power-Mox" Series
with Ferrule end caps



"Power-Mox" Series with 1/4 - 20 threaded end caps



To specify Power-Mox Dividers, please see our website at: www.ohmite.com/dividers

ORDERING INFORMATION

A complete description of the Power-MOX Divider is required. EXAMPLE:

 $RT = 500M\Omega 5\%$

 $R1 = 499.5M\Omega 5\%$

 $R2 = 500 \text{K}\Omega 1\%$

Ratio = RT / R2 = 1,000: 1, 1%

To specify Power-Mox Dividers, please see our website at **www.ohmite.com/dividers**. Contact Ohmite for custom configurations.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Thick Film Resistors - Through Hole category:

Click to view products by Ohmite manufacturer:

Other Similar products are found below:

```
M8340104M4701GCD03 M8340105K3300GGD03 M8340105K3922FGD03 M8340106K1002JCD03 M8340107K1002GGD03 M8340107K1152FGD03 M8340107K2701GCD03 M8340107M2002GCD03 M8340108K1000GCD03 M8340108K5601GCD03 M8340108M2203GCD03 M8340109K1002JCD03 M8340109K2001GCD03 M8340109K5101GGD03 FHV05010M0FKRB MOX-2-125005F MP850-3.00-1% MS220-1K-1% hte24511kf SM-SP093 ARC3.11 2M J A M8340105K1001GCD03 M8340105K3002GGD03 M8340105M1002JGD03 M8340107K2001GGD03 M8340107K5101GGD03 M8340107K5600GGD03 M8340108K4990FGD03 M8340108K49R9FGD03 M8340108M10R0GGD03 M8340109K2202GGD03 M8340109K5601GCD03 MOX-GRD-001 MOX-SP020 MOX-SP025E M8340107K2001GCD03 M8340102M4701GBD04 M8340102K1002GBD04 M8340102K1002GAD04 M8340109K2002GGD03 M8340108K22R0GGD03 M8340107M5100GGD03 OE1305 WMHP100-R22J M8340104K39R2FCD03 M8340106MA012JHD03 M8340107K1003GGD03 MS126-9.09K-0.1% MS126-249K-0.1% MS-221-82R5
```